

# AVOW ADVANCED PRO 1



## SPECS

ΣΚΕΛΕΤΟΣ	
ΜΕΓΕΘΗ	XS, S, M
ΧΡΩΜΑΤΑ	Terracotta/Carbon
ΣΚΕΛΕΤΟΣ	Advanced-Grade Composite
ΠΙΡΟΥΝΙ	Advanced-Grade Composite, alloy OverDrive steerer
ΑΝΑΡΤΗΣΗ	N/A
ΕΞΑΡΤΗΜΑΤΑ	
ΤΙΜΟΝΙ	Liv Avow Carbon XXS:36cm, XS:36cm, S:38cm, M:40cm, L:42cm
GRIPS	Liv Contact Gel
ΛΑΙΜΟΣ ΤΙΜΟΝΙΟΥ	Liv Avow Alloy XS:80mm, S:90mm, M:100mm,
ΛΑΙΜΟΣ ΣΈΛΛΑΣ	Liv Avow Carbon XS:TKmm, S:TKmm, M:TKmm,
ΣΈΛΛΑ	ISM PS1.0
ΠΕΝΤΑΛ	N/A
ΜΕΤΑΔΟΣΗ	
ΛΕΒΙΕ ΤΑΧΥΤΗΤΩΝ	Shimano Ultegra Di2 ST-R8170
ΝΤΕΡΑΓΙΕΡ ΕΜΠΡΟΣΘΙΟ	Shimano Ultegra Di2 FD-R8150
ΝΤΕΡΑΓΙΕΡ ΟΠΙΣΘΙΟ.	Shimano Ultegra Di2 RD-R8150
ΦΡΈΝΑ	Giant SpeedControl SL
ΜΑΝΈΤΤΕΣ ΦΡΈΝΩΝ	Giant Trinity
CASETTE Ή ΕΛΕΥΘΕΡΟ	Shimano Ultegra, 12-speed, 11x30
ΑΛΥΣΙΔΑ	Shimano Ultegra
ΔΙΣΚΟΒΡΑΧΙΩΝΑΣ	Shimano Ultegra, 36/52 XS:160mm, S:165mm, M:165mm
ΒΟΤΤΟΜ BRACKET	Shimano, press fit

WHEELS	
ΣΤΕΦΑΝΙΑ	Giant P-A2 wheelset
ΚΕΝΤΡΑ	Giant P-A2 wheelset
ΑΚΤΙΝΕΣ	Giant P-A2 wheelset
ΕΛΑΣΤΙΚΑ	Giant Gavia AC Lite, tubeless, 700x25c (26.5mm), folding
EXTRAS	integrated hydration, integrated food storage, misc fairings, AeroVault System, 25mm max tire size

## ΓΕΩΜΕΤΡΙΑ

ΣΚΕΛΕΤΟΣ	XXS	XS	S	M
Seat Tube Length (mm)	450	480	510	530
Seat Tube Angle	77,0°	77,0°	77,0°	77,0°
Top Tube Length (mm)	480	500	515	540
Head Tube Length (mm)	80	80	95	125
Head Tube Angle	71,5°	72,0°	72,5°	72,5°
Fork Rake (mm)	40	40	40	40
Trail (mm)	62	68	64	64
Wheelbase (mm)	949	961	974	1001
Chain Stay Length (mm)	405	405	405	405
Bottom Bracket Drop (mm)	64	75	75	75
Stack (mm)	442	490	504	534
Reach (mm)	378	387	398	417
Stand Over Height (mm)	708	740	767	788
Handlebar Width (mm)	400	400	400	400
Stem Length (mm)	80	80	80	80
Crank Length (mm)	160	165	165	165
Wheel Size	700C	700C	700C	700C

Όλες οι προδιαγραφές είναι δυνατό να αλλάξουν χωρίς πρότερη ειδοποίηση