

AVOW ADVANCED PRO 1



SPECS

FRAME	
SIZES	XS, S, M
COLORS	Terracotta/Carbon
FRAME	Advanced-Grade Composite
FORK	Advanced-Grade Composite, alloy OverDrive steerer
SHOCK	N/A
COMPONENTS	
HANDLEBAR	Liv Avow Carbon XXS:36cm, XS:36cm, S:38cm, M:40cm, L:42cm
GRIPS	Liv Contact Gel
STEM	Liv Avow Alloy XS:80mm, S:90mm, M:100mm,
SEATPOST	Liv Avow Carbon XS:TKmm, S:TKmm, M:TKmm,
SADDLE	ISM PS1.0
PEDALS	N/A
DRIVETRAIN	
SHIFTERS	Shimano Ultegra Di2 ST-R8170
FRONT DERAILLEUR	Shimano Ultegra Di2 FD-R8150
REAR DERAILLEUR	Shimano Ultegra Di2 RD-R8150
BRAKES	Giant SpeedControl SL
BRAKE LEVERS	Giant Trinity
CASSETTE	Shimano Ultegra, 12-speed, 11x30
CHAIN	Shimano Ultegra
CRANKSET	Shimano Ultegra, 36/52 XS:160mm, S:165mm, M:165mm
BOTTOM BRACKET	Shimano, press fit

WHEELS	
RIMS	Giant P-A2 wheelset
HUBS	Giant P-A2 wheelset
SPOKES	Giant P-A2 wheelset
TIRES	Giant Gavia AC Lite, tubeless, 700x25c (26.5mm), folding
EXTRAS	integrated hydration, integrated food storage, misc fairings, AeroVault System, 25mm max tire size

GEOMETRY

FRAME	XXS	XS	S	M
Seat Tube Length (mm)	450	480	510	530
Seat Tube Angle	77,0°	77,0°	77,0°	77,0°
Top Tube Length (mm)	480	500	515	540
Head Tube Length (mm)	80	80	95	125
Head Tube Angle	71,5°	72,0°	72,5°	72,5°
Fork Rake (mm)	40	40	40	40
Trail (mm)	62	68	64	64
Wheelbase (mm)	949	961	974	1001
Chain Stay Length (mm)	405	405	405	405
Bottom Bracket Drop (mm)	64	75	75	75
Stack (mm)	442	490	504	534
Reach (mm)	378	387	398	417
Stand Over Height (mm)	708	740	767	788
Handlebar Width (mm)	400	400	400	400
Stem Length (mm)	80	80	80	80
Crank Length (mm)	160	165	165	165
Wheel Size	700C	700C	700C	700C

All specifications listed are subject to change without notice.