

# AVOW ADVANCED PRO 1



## SPECS

RAMME	
STØRRELSE	XS, S, M
FARGE	Terracotta/Carbon
RAMME	Advanced-Grade Composite
GAFFEL	Advanced-Grade Composite, alloy OverDrive steerer
DEMPER	N/A
KOMPONENTER	
STYRE	Liv Avow Carbon XXS:36cm, XS:36cm, S:38cm, M:40cm, L:42cm
GRIPS	Liv Contact Gel
STYRSTEM	Liv Avow Alloy XS:80mm, S:90mm, M:100mm,
SETEPINNE	Liv Avow Carbon XS:TKmm, S:TKmm, M:TKmm,
SADEL	ISM PS1.0
PEDALER	N/A
DRIVVERK	
GIRHENDLER	Shimano Ultegra Di2 ST-R8170
FRONTGIR	Shimano Ultegra Di2 FD-R8150
BAKGIR	Shimano Ultegra Di2 RD-R8150
BREMSER	Giant SpeedControl SL
BREMSEHENDLER	Giant Trinity
KASSETT	Shimano Ultegra, 12-speed, 11x30
KJEDE	Shimano Ultegra
KRANK	Shimano Ultegra, 36/52 XS:160mm, S:165mm, M:165mm
BOTTOM BRACKET	Shimano, press fit

HJUL	
FELG	Giant P-A2 wheelset
NAV	Giant P-A2 wheelset
EIKE	Giant P-A2 wheelset
DEKK	Giant Gavia AC Lite, tubeless, 700x25c (26.5mm), folding
EXTRAS	integrated hydration, integrated food storage, misc fairings, AeroVault System, 25mm max tire size

## GEOMETRI

RAMME	XXS	XS	S	M
Seat Tube Length (mm)	450	480	510	530
Seat Tube Angle	77,0°	77,0°	77,0°	77,0°
Top Tube Length (mm)	480	500	515	540
Head Tube Length (mm)	80	80	95	125
Head Tube Angle	71,5°	72,0°	72,5°	72,5°
Fork Rake (mm)	40	40	40	40
Trail (mm)	62	68	64	64
Wheelbase (mm)	949	961	974	1001
Chain Stay Length (mm)	405	405	405	405
Bottom Bracket Drop (mm)	64	75	75	75
Stack (mm)	442	490	504	534
Reach (mm)	378	387	398	417
Stand Over Height (mm)	708	740	767	788
Handlebar Width (mm)	400	400	400	400
Stem Length (mm)	80	80	80	80
Crank Length (mm)	160	165	165	165
Wheel Size	700C	700C	700C	700C

Alle spesifikasjonene kan endres uten varsel.