

# AVOW ADVANCED PRO 1



## SPECS

FRAME	
<b>SIZES</b>	XS, S, M
<b>COLORS</b>	Dark Iridescent
<b>FRAME</b>	Advanced-Grade Composite
<b>FORK</b>	Advanced-Grade Composite, alloy OverDrive steerer
<b>SHOCK</b>	N/A
COMPONENTS	
<b>HANDLEBAR</b>	Liv Avow, carbon base bar
<b>STEM</b>	Avow, alloy
<b>SEATPOST</b>	Avow, composite
<b>SADDLE</b>	ISM PS1.0
<b>PEDALS</b>	N/A
DRIVETRAIN	
<b>SHIFTERS</b>	Shimano Ultegra Di2
<b>FRONT DERAILLEUR</b>	Shimano Ultegra Di2
<b>REAR DERAILLEUR</b>	Shimano Ultegra Di2
<b>BRAKES</b>	Giant SpeedControl SL
<b>BRAKE LEVERS</b>	Giant Trinity
<b>CASSETTE</b>	Shimano Ultegra, 11x30
<b>CHAIN</b>	KMC X11SL-1
<b>CRANKSET</b>	Shimano Ultegra 36/52, Giant Power Pro power meter
<b>BOTTOM BRACKET</b>	Shimano, press fit

WHEELS	
<b>RIMS</b>	Giant P-A2 wheelset
<b>HUBS</b>	Giant P-A2 wheelset
<b>SPOKES</b>	Giant P-A2 wheelset
<b>TIRES</b>	Giant AC 1, 700x25c, tubeless
<b>EXTRAS</b>	integrated hydration, integrated food storage, AeroVault system

## GEOMETRY

FRAME	XS	S	M
Seat Tube Length (mm)	480	510	530
Seat Tube Angle	77,0°	77,0°	77,0°
Top Tube Length (mm)	500	515	540
Head Tube Length (mm)	80	95	125
Head Tube Angle	72,0°	72,5°	72,5°
Fork Rake (mm)	40	40	40
Trail (mm)	68	64	64
Wheelbase (mm)	961	974	1001
Chain Stay Length (mm)	405	405	405
Bottom Bracket Drop (mm)	75	75	75
Stack (mm)	490	504	534
Reach (mm)	387	398	417
Stand Over Height (mm)	740	767	788
Handlebar Width (mm)	400	400	400
Stem Length (mm)	80	80	80
Crank Length (mm)	165	165	165
Wheel Size	700C	700C	700C

All specifications listed are subject to change without notice.