

AVOW ADVANCED PRO 1



SPECS

CADRU	
MARIMI	XS, S, M
CULORI	Terracotta/Carbon
CADRU	Advanced-Grade Composite
FURCA	Advanced-Grade Composite, alloy OverDrive steerer
SOC	N/A
COMPONENTE	
GHIDON	Liv Avow Carbon XXS:36cm, XS:36cm, S:38cm, M:40cm, L:42cm
GRIPS	Liv Contact Gel
PIPA	Liv Avow Alloy XS:80mm, S:90mm, M:100mm,
TIJA SA	Liv Avow Carbon XS:TKmm, S:TKmm, M:TKmm,
SA	ISM PS1.0
PEDALE	N/A
SISTEMUL DE SCHIMBARE A VITEZELOR	
MANETE SCHIMBATOR	Shimano Ultegra Di2 ST-R8170
SCHIMBATOR FATA	Shimano Ultegra Di2 FD-R8150
SCHIMBATOR SPATE	Shimano Ultegra Di2 RD-R8150
FRANE	Giant SpeedControl SL
MANETE FRANA	Giant Trinity
PINIOANE	Shimano Ultegra, 12-speed, 11x30
LANT	Shimano Ultegra
ANGRENAJ	Shimano Ultegra, 36/52 XS:160mm, S:165mm, M:165mm
BOTTOM BRACKET	Shimano, press fit

ROTI	
JANTE	Giant P-A2 wheelset
BUTUCI	Giant P-A2 wheelset
SPITE	Giant P-A2 wheelset
ANVELOPE	Giant Gavia AC Lite, tubeless, 700x25c (26.5mm), folding
EXTRAS	integrated hydration, integrated food storage, misc fairings, AeroVault System, 25mm max tire size

GEOMETRIE

CADRU	XXS	XS	S	M
Seat Tube Length (mm)	450	480	510	530
Seat Tube Angle	77,0°	77,0°	77,0°	77,0°
Top Tube Length (mm)	480	500	515	540
Head Tube Length (mm)	80	80	95	125
Head Tube Angle	71,5°	72,0°	72,5°	72,5°
Fork Rake (mm)	40	40	40	40
Trail (mm)	62	68	64	64
Wheelbase (mm)	949	961	974	1001
Chain Stay Length (mm)	405	405	405	405
Bottom Bracket Drop (mm)	64	75	75	75
Stack (mm)	442	490	504	534
Reach (mm)	378	387	398	417
Stand Over Height (mm)	708	740	767	788
Handlebar Width (mm)	400	400	400	400
Stem Length (mm)	80	80	80	80
Crank Length (mm)	160	165	165	165
Wheel Size	700C	700C	700C	700C

Toate specificatiile enumerate se pot schimba fara notificare prealabila.