AVOW ADVANCED PRO 2



SPECS

FRAME	
SIZES	XS, S, M
COLORS	Echeveria
FRAME	Advanced-Grade Composite
FORK	Advanced-Grade Composite, alloy OverDrive steerer
SHOCK	N/A
COMPONENTS	
HANDLEBAR	Liv Avow, carbon base bar
STEM	Avow, alloy
SEATPOST	Avow, composite
SADDLE	ISM PS1.0
PEDALS	N/A
DRIVETRAIN	
SHIFTERS	Shimano SL-BSR1
FRONT DERAILLEUR	Shimano Ultegra
REAR DERAILLEUR	Shimano Ultegra
BRAKES	Giant SpeedControl SL
BRAKE LEVERS	Giant Trinity
CASSETTE	Shimano Ultegra, 11x30
CHAIN	KMC X11SL-1
CRANKSET	Shimano Ultegra 36/52, Giant Power Pro power meter
BOTTOM BRACKET	Shimano, press fit

WHEELS	
RIMS	Giant P-A2 wheelset
HUBS	Giant P-A2 wheelset
SPOKES	Giant P-A2 wheelset
TIRES	Giant AC 1, 700x25c, tubeless
EXTRAS	integrated hydration, integrated food storage, AeroVault system, tubeless prepared

GEOMETRY

FRAME	XS	S	M
Seat Tube Length (mm)	480	510	530
Seat Tube Angle	77,0°	77,0°	77,0°
Top Tube Length (mm)	500	515	540
Head Tube Length (mm)	80	95	125
Head Tube Angle	72,0°	72,5°	72,5°
Fork Rake (mm)	40	40	40
Trail (mm)	68	64	64
Wheelbase (mm)	961	974	1001
Chain Stay Length (mm)	405	405	405
Bottom Bracket Drop (mm)	75	75	75
Stack (mm)	490	504	534
Reach (mm)	387	398	417
Stand Over Height (mm)	740	767	788
Handlebar Width (mm)	400	400	400
Stem Length (mm)	80	80	80
Crank Length (mm)	165	165	165
Wheel Size	700C	700C	700C

All specifications listed are subject to change without notice.