

AVOW ADVANCED PRO 2



SPECS

FRAME	
SIZES	XS, S, M
COLOURS	Milky Way
FRAME	Advanced-Grade Composite
FORK	Advanced-Grade Composite, alloy OverDrive steerer
SHOCK	N/A
COMPONENTS	
HANDLEBAR	Liv Avow Carbon XS:36cm, S:38cm, M:40cm
GRIPS	Liv Contact Gel
STEM	Liv Avow Alloy XS:80mm, S:90mm, M:100mm
SEATPOST	Liv Avow Carbon
SADDLE	Liv Contact SL Tri
PEDALS	N/A
DRIVETRAIN	
SHIFTERS	Shimano SL-BSR1
FRONT DERAILLEUR	Shimano Ultegra
REAR DERAILLEUR	Shimano Ultegra
BRAKES	Giant SpeedControl SL
BRAKE LEVERS	Giant Trinity
CASSETTE	Shimano Ultegra, 11-speed, 11x30
CHAIN	KMC X11SL-1
CRANKSET	Shimano Ultegra, 36/52 w/ Power Pro power meter XS:165mm, S:165mm, M:165mm
BOTTOM BRACKET	Shimano, press fit

WHEELS	
RIMS	Giant P-R2 wheelset
HUBS	Giant P-R2 wheelset
SPOKES	Giant P-R2 wheelset
TIRES	Giant Gavia AC Lite, tubeless, 700x25c (26.5mm), folding
EXTRAS	Integrated hydration, integrated food storage, misc fairings, AeroVault System, 25mm max tyre size

Price: \$5,999.00

GEOMETRY

FRAME	XS	S	M
Seat Tube Length (mm)	480	510	530
Seat Tube Angle	77.0°	77.0°	77.0°
Top Tube Length (mm)	500	515	540
Head Tube Length (mm)	80	95	125
Head Tube Angle	72.0°	72.5°	72.5°
Fork Rake (mm)	40	40	40
Trail (mm)	68	64	64
Wheelbase (mm)	961	974	1001
Chain Stay Length (mm)	405	405	405
Bottom Bracket Drop (mm)	75	75	75
Stack (mm)	490	504	534
Reach (mm)	387	398	417
Stand Over Height (mm)	740	767	788
Stem Length (mm)	80	80	80
Crank Length (mm)	165	165	165
Wheel Size	700C	700C	700C

Please note that our specifications may be impacted by running substitution changes, we highly recommend confirming the specifications of our products with your local retailer at the time of sale if purchasing in-store. *Recommended Retail Prices are subject to change without notice and may vary from store to store depending on freight and assembly costs.