AVOW ADVANCED SL 2



SPECIFICATIES

FRAME	
MATEN	XXS, XS, S, M
KLEUREN	Pearl White/Chrome
FRAME	Advanced SL-grade composite, 12x142mm thru-axle, disc
VOORVORK	Advanced SL-grade composite, full-composite steerer, 12x100mm, disc
ONDERDELEN	
STUUR	Giant Base Bar with integrated stem and Sync rest set 10- & 15-degree extension wedge
HANDVATTEN	Liv Stratus Lite 2.0
STUURPEN	Giant Base Bar with integrated stem and Sync rest set 10- & 15-degree extension wedge
ZADELPEN	Avow Composite
ZADEL	Liv Contact SL Tri
ARMSTEUNSET	Sync armrest set
AFMONTAGE	
SHIFTERS	SRAM eTap Clics, extension mounted SRAM eTap Blips, basebar mounted
VOORDERAILLEUR	SRAM Rival eTap AXS
ACHTERDERAILLEUR	SRAM Rival eTap AXS E1
REMMEN	SRAM Rival Aero eTap hydraulic, SRAM PaceLine rotors [F]160mm, [R]140mm
REMHENDELS	SRAM Rival Aero AXS hydraulic
CASSETTE	SRAM Rival E1, 12-speed, 10x36
AANDRIJVING	SRAM Rival E1
CRANKSET	SRAM Rival E1 AXS, 35/48 with SRAM power meter XXS: 160mm, XS: 160mm, S: 160mm, M: 165mm
BOTTOM BRACKET	SRAM DUB, press fit

WIELSET	
VELGEN	Giant SLR 2 50 WheelSystem, [F] 50mm, [R] 50mm
NAVEN	[F] Giant Alloy, CenterLock, 12mm thru-axle [R] Giant Alloy, 3 pawl 30t driver, CenterLock, 12mm thru-axle
SPAKEN	stainless
BANDEN	CADEX Aero Tubeless, 700x28c, folding, tubeless
EXTRA'S	bento box top tube storage, hydration kit, computer mount, tubeless prepared, 30mm max tire size
LIMITS	
MAXIMALE BANDENVRIJHEID	30mm

Adviesprijs: € 7.499,00

GEOMETRIE

FRAME	XS	S	M
Zitbuis Lengte (mm)	477	508	539
Zitbuis Hoek	77,0°	77,0°	77,0°
Frame Lengte (horizontaal) (mm)	510	530	554
Balhoofdbuis Lengte (mm)	85	105	125
Balhoofdbuis Hoek	72,0°	73,0°	73,0°
Vork Sprong (mm)	40	40	40
Naloop (mm)	69	63	63
Wielbasis (mm)	974	988	1013
Liggende achtervork lengte (mm)	405	405	405
Bottom Bracket Drop (mm)	70	70	70
Stack (mm)	490	513	532
Reach (mm)	397	412	432
Stand Over Height (mm)	758	786	814
Stuur breedte (mm)	400	400	400
Wielmaat	700C	700C	700C
Arm Pad Stack	(TRI) 629-709 | (TT) 582-662	(TRI) 653-733 | (TT) 605-685	(TRI) 672-752 | (TT) 6
Arm Pad Reach	(TRI) 323-398 | (TT) 339-414	(TRI) 340-415 | (TT) 355-430	(TRI) 360-435 | (TT) 3

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder vooraankondiging wijzigen.