

# AVOW ADVANCED SL



## СПЕЦИФИКАЦИИ

РАМКА	
РАЗМЕР	XXS, XS, S, M
ЦВЯТ	Carbon
РАМКА	Advanced SL-grade composite, 12x142mm thru-axle, disc
ВИЛКА	Advanced SL-grade composite, full-composite steerer, 12x100mm, disc
ЗАДЕН АМОРТИСЬОР	N/A
КОМПОНЕНТИ	
КОРМИЛО	AeroDrive base bar with Sync armrest set, 10- and 15-degree extension wedge
ГРИПОВЕ	Liv Stratus Lite 2.0
ЛАПА	AeroDrive integrated stem
КОЛЧЕ ЗА СЕДАЛКА	Liv Avow Composite
СЕДАЛКА	Liv Contact SL Tri
ARM REST KIT	Sync armrest set
DRIVETRAIN	
КОМАНДИ	SRAM eTap Clics, extension mountedSRAM eTap Blips, basebar mounted
ПРЕДЕН ДЕРАЙЛЪОР	SRAM Rival eTap AXS
ЗАДЕН ДЕРАЙЛЪОР	SRAM Rival eTap AXS
СПИРАЧКИ	SRAM Rival eTap hydraulic, SRAM PaceLine rotors [F]160mm, [R]140mm
РЪКОХВАТКИ ЗА СПИРАЧКИ	SRAM S-900 Aero hydraulic
КАСЕТА	SRAM Rival XG-1250, 12-speed, 10x36
ВЕРИГА	SRAM Rival D1
КУРБЕЛ	SRAM Rival, 35/48 with Giant Power Halo power meter XXS: 160mm, XS: 160mm, S: 160mm, M: 165mm, L: 165mm
СРЕДНА КАСЕТА	SRAM DUB, press fit

КАПЛИ	
ШИНИ	Giant SLR 2 50 WheelSystem, [F]50mm, [R]50mm
ГЛАВИНИ	[F] Giant Alloy, CenterLock, 12mm thru-axle [R] Giant Alloy, 3 pawl 30t driver, CenterLock, 12mm thru-axle
СПИЦИ	SAPIM Sprint
ГУМИ	CADEX Aero, tubeless, 700x25c (26.5mm), folding
ЕКСТРИ	bento box top tube storage, hydration kit, computer mount, tubeless prepared, 30mm max tire size
ЛИМИТИ	
MAX TIRE CLEARANCE	30mm

## ГЕОМЕТРИЯ

РАМКА	XXS	XS	S
Seat Tube Length (mm)	440	477	508
Seat Tube Angle	77,0°	77,0°	77,0°
Top Tube Length (mm)	493	510	530
Head Tube Length (mm)	65	85	105
Head Tube Angle	71,0°	72,0°	73,0°
Fork Rake (mm)	40	40	40
Trail (mm)	79	69	63
Wheelbase (mm)	969	974	988
Chain Stay Length (mm)	405	405	405
Bottom Bracket Drop (mm)	70	70	70
Stack (mm)	467	490	513
Обсер (mm)	387	397	412
Stand Over Height (mm)	733	758	786
Ширина на Кормило (mm)	400	400	400
Размер на Каплите	700C	700C	700C
Arm Pad Stack	(TRI) 604-686   (TT) 556-640	(TRI) 629-709   (TT) 582-662	(TRI) 653-733   (TT) 605-686
Arm Pad Reach	(TRI) 309-383   (TT) 326-400	(TRI) 323-398   (TT) 339-414	(TRI) 340-415   (TT) 355-430

All specifications listed are subject to change without notice.