

# AVOW ADVANCED SL



## SPECIFIKATIONER

RAMME	
STØRRELSER	XS, S, M
FARVER	Carbon
RAMME	Advanced SL-grade composite, 12x142mm thru-axle, disc
FORGAFFEL	Advanced SL-grade composite, full-composite steerer, 12x100mm, disc
BAGDÆMPER	N/A
KOMPONENTER	
STYR	AeroDrive base bar with Sync armrest set, 10- and 15-degree extension wedge
GREB / STYRBÅND	Liv Stratus Lite 2.0
FREMPIND	AeroDrive integrated stem
SADELPIND	Liv Avow Composite
SADEL	Liv Contact SL Tri
ARM REST SÆT	Sync armrest set
GEARGRUPPE	
SKIFTEGREB	SRAM eTap Clics, extension mountedSRAM eTap Blips, basebar mounted
FORSKIFTER	SRAM Rival eTap AXS
BAGSKIFTER	SRAM Rival eTap AXS
BREMSE	SRAM Rival eTap hydraulic, SRAM PaceLine rotors [F]160mm, [R]140mm
BREMSEGREB	SRAM S-900 Aero hydraulic
KASSETTE	SRAM Rival XG-1250, 12-speed, 10x36
KÆDE	SRAM Rival D1
KRANKSÆT	SRAM Rival, 35/48 with Giant Power Halo power meter XXS: 160mm, XS: 160mm, S: 160mm, M: 165mm, L: 165mm
KRANKBOKS	SRAM DUB, press fit

HJUL	
FÆLGE	Giant SLR 2.50 WheelSystem, [F]50mm, [R]50mm
NAV	[F] Giant Alloy, CenterLock, 12mm thru-axle [R] Giant Alloy, 3 pawl 30t driver, CenterLock, 12mm thru-axle
EGER	SAPIM Sprint
DÆK	CADEX Aero, tubeless, 700x25c (26.5mm), folding
EKSTRA	bento box top tube storage, hydration kit, computer mount, tubeless prepared, 30mm max tire size
GRÆNSER	
MAX DÆKSTØRRELSE	30mm

Pris: 63.599,00 kr.

## GEOMETRI

RAMME	XS	S	M
Sadelrørslængde (mm)	477	508	538
Sadelrørsvinkel	77,0°	77,0°	77,0°
Overrørslængde (mm)	510	530	554
Kronrørslængde (mm)	85	105	125
Kronrørsvinkel	72,0°	73,0°	73,0°
Forgaffel fremspring (rake) (mm)	40	40	40
Sti (mm)	69	63	63
Akselafstand (mm)	974	988	1013
Kædestagslængde (mm)	405	405	405
Krankboks drop (mm)	70	70	70
Stack (mm)	490	513	532
Reach (mm)	397	412	432
Skridthøjde (mm)	758	786	814
Styrbredde (mm)	400	400	400
Hjulstørrelse	700C	700C	700C
Armstøtte stack	(TRI) 629-709   (TT) 582-662	(TRI) 653-733   (TT) 605-685	(TRI) 672-752   (TT) 629-709
Armstøtte reach	(TRI) 323-398   (TT) 339-414	(TRI) 340-415   (TT) 355-430	(TRI) 360-435   (TT) 375-450

Alle de anførte specifikationer kan ændres uden varsel.