

AVOW ADVANCED SL



SPECS

ΣΚΕΛΕΤΟΣ	
ΜΕΓΕΘΗ	XXS, XS, S, M
ΧΡΩΜΑΤΑ	Carbon
ΣΚΕΛΕΤΟΣ	Advanced SL-grade composite, 12x142mm thru-axle, disc
ΠΙΡΟΥΝΙ	Advanced SL-grade composite, full-composite steerer, 12x100mm, disc
ΑΝΑΡΤΗΣΗ	N/A
ΕΞΑΡΤΗΜΑΤΑ	
ΤΙΜΟΝΙ	AeroDrive base bar with Sync armrest set, 10- and 15-degree extension wedge
GRIPS	Liv Stratus Lite 2.0
ΛΑΙΜΟΣ ΤΙΜΟΝΙΟΥ	AeroDrive integrated stem
ΛΑΙΜΟΣ Σ'ΕΛΛΑΣ	Liv Avow Composite
Σ'ΕΛΛΑ	Liv Contact SL Tri
ARM REST KIT	Sync armrest set
ΜΕΤΑΔΟΣΗ	
ΛΕΒΙΕ ΤΑΧΥΤΗΤΩΝ	SRAM eTap Clics, extension mountedSRAM eTap Blips, basebar mounted
ΝΤΕΡΑΓ'ΕΡ ΕΜΠΡΟΣΘΙΟ	SRAM Rival eTap AXS
ΝΤΕΡΑΓ'ΕΡ ΟΠΙΣΘΙΟ.	SRAM Rival eTap AXS
ΦΡΕΝΑ	SRAM Rival eTap hydraulic, SRAM PaceLine rotors [F]160mm, [R]140mm
ΜΑΝΕΤΤΕΣ ΦΡΕΝΩΝ	SRAM S-900 Aero hydraulic
CASETTE Η ΕΛΕΥΘΕΡΟ	SRAM Rival XG-1250, 12-speed, 10x36
ΑΛΥΣΙΔΑ	SRAM Rival D1
ΔΙΣΚΟΒΡΑΧΙΩΝΑΣ	SRAM Rival, 35/48 with Giant Power Halo power meter XXS: 160mm, XS: 160mm, S: 160mm, M: 165mm, L: 165mm
BOTTOM BRACKET	SRAM DUB, press fit

WHEELS	
ΣΤΕΦΑΝΙΑ	Giant SLR 2 50 WheelSystem, [F]50mm, [R]50mm
ΚΕΝΤΡΑ	[F] Giant Alloy, CenterLock, 12mm thru-axle [R] Giant Alloy, 3 pawl 30t driver, CenterLock, 12mm thru-axle
ΑΚΤΙΝΕΣ	SAPIM Sprint
ΕΛΑΣΤΙΚΑ	CADEX Aero, tubeless, 700x25c (26.5mm), folding
EXTRAS	bento box top tube storage, hydration kit, computer mount, tubeless prepared, 30mm max tire size
LIMITS	
MAX TIRE CLEARANCE	30mm

ΓΕΩΜΕΤΡΙΑ

ΣΚΕΛΕΤΟΣ	XXS	XS	S
Seat Tube Length (mm)	440	477	508
Seat Tube Angle	77,0°	77,0°	77,0°
Top Tube Length (mm)	493	510	530
Head Tube Length (mm)	65	85	105
Head Tube Angle	71,0°	72,0°	73,0°
Fork Rake (mm)	40	40	40
Trail (mm)	79	69	63
Wheelbase (mm)	969	974	988
Chain Stay Length (mm)	405	405	405
Bottom Bracket Drop (mm)	70	70	70
Stack (mm)	467	490	513
Reach (mm)	387	397	412
Stand Over Height (mm)	733	758	786
Handlebar Width (mm)	400	400	400
Wheel Size	700C	700C	700C
Arm Pad Stack	(TRI) 604-686 (TT) 556-640	(TRI) 629-709 (TT) 582-662	(TRI) 653-733 (TT) 605-688
Arm Pad Reach	(TRI) 309-383 (TT) 326-400	(TRI) 323-398 (TT) 339-414	(TRI) 340-415 (TT) 355-430

Όλες οι προδιαγραφές είναι δυνατό να αλλάξουν χωρίς πρότερη ειδοποίηση