

AVOW ADVANCED SL



SPECS

FRAME	
SIZES	XXS, XS, S, M
COLORS	Carbon
FRAME	Advanced SL-grade composite, 12x142mm thru-axle, disc
FORK	Advanced SL-grade composite, full-composite steerer, 12x100mm, disc
SHOCK	N/A
COMPONENTS	
HANDLEBAR	AeroDrive base bar with Sync armrest set, 10- and 15-degree extension wedge
GRIPS	Liv Stratus Lite 2.0
STEM	AeroDrive integrated stem
SEATPOST	Liv Avow Composite
SADDLE	Liv Contact SL Tri
ARM REST KIT	Sync armrest set
DRIVETRAIN	
SHIFTERS	SRAM eTap Clics, extension mountedSRAM eTap Blips, basebar mounted
FRONT DERAILLEUR	SRAM Rival eTap AXS
REAR DERAILLEUR	SRAM Rival eTap AXS
BRAKES	SRAM Rival eTap hydraulic, SRAM PaceLine rotors [F]160mm, [R]140mm
BRAKE LEVERS	SRAM S-900 Aero hydraulic
CASSETTE	SRAM Rival XG-1250, 12-speed, 10x36
CHAIN	SRAM Rival D1
CRANKSET	SRAM Rival, 35/48 with Giant Power Halo power meter XXS: 160mm, XS: 160mm, S: 160mm, M: 165mm, L: 165mm
BOTTOM BRACKET	SRAM DUB, press fit

WHEELS	
RIMS	Giant SLR 2 50 WheelSystem, [F]50mm, [R]50mm
HUBS	[F] Giant Alloy, CenterLock, 12mm thru-axle [R] Giant Alloy, 3 pawl 30t driver, CenterLock, 12mm thru-axle
SPOKES	SAPIM Sprint
TIRES	CADEX Aero, tubeless, 700x25c (26.5mm), folding
EXTRAS	bento box top tube storage, hydration kit, computer mount, tubeless prepared, 30mm max tire size
LIMITS	
MAX TIRE CLEARANCE	30mm

Recommended Retail Price: **\$9,900.00**

GEOMETRY

FRAME	XS	S	M
Seat Tube Length (inch)	18.8	20	21.2
Seat Tube Angle	77.0°	77.0°	77.0°
Top Tube Length (inch)	20.1	20.9	21.8
Head Tube Length (inch)	3.3	4.1	4.9
Head Tube Angle	72.0°	73.0°	73.0°
Fork Rake (inch)	1.6	1.6	1.6
Trail (inch)	2.7	2.5	2.5
Wheelbase (inch)	38.3	38.9	39.9
Chain Stay Length (inch)	15.9	15.9	15.9
Bottom Bracket Drop (inch)	2.8	2.8	2.8
Stack (inch)	19.3	20.2	20.9
Reach (inch)	15.6	16.2	17
Stand Over Height (inch)	29.8	30.9	32
Handlebar Width (inch)	15.7	15.7	15.7
Wheel Size	700C	700C	700C
Arm Pad Stack	(TRI) 629-709 (TT) 582-662	(TRI) 653-733 (TT) 605-685	(TRI) 672-752 (TT) 624-707
Arm Pad Reach	(TRI) 323-398 (TT) 339-414	(TRI) 340-415 (TT) 355-430	(TRI) 360-435 (TT) 375-450

**All specifications and prices listed are subject to change without notice. Actual weight may vary due to manufacturing tolerances, color variations, frame size and variability in production components.*