

AVOW ADVANCED SL



ESPECIFICACIONES

CUADRO	
TALLAS	XXS, XS, S, M
COLORES	Carbon
CUADRO	Advanced SL-grade composite, 12x142mm thru-axle, disc
TIJERA	Advanced SL-grade composite, full-composite steerer, 12x100mm, disc
AMORTIGUADOR	N/A
COMPONENTES	
MANUBRIO	AeroDrive base bar with Sync armrest set, 10- and 15-degree extension wedge
GRIPS	Liv Stratus Lite 2.0
POTENCIA	AeroDrive integrated stem
POSTE DE ASIENTO	Liv Avow Composite
ASIENTO	Liv Contact SL Tri
ARM REST KIT	Sync armrest set
TRANSMISIÓN	
MANETAS DE CAMBIO	SRAM eTap Clics, extension mountedSRAM eTap Blips, basebar mounted
DESVIADOR	SRAM Rival eTap AXS
CAMBIO TRASERO	SRAM Rival eTap AXS
FRENOS	SRAM Rival eTap hydraulic, SRAM PaceLine rotors [F]160mm, [R]140mm
PALANCAS DE FRENOS	SRAM S-900 Aero hydraulic
CASSETTE	SRAM Rival XG-1250, 12-speed, 10x36
CADENA	SRAM Rival D1
MULTIPLICACIÓN	SRAM Rival, 35/48 with Giant Power Halo power meter XXS: 160mm, XS: 160mm, S: 160mm, M: 165mm, L: 165mm
EJE DE CENTRO	SRAM DUB, press fit

RUEDAS	
RUEDAS	Giant SLR 2 50 WheelSystem, [F]50mm, [R]50mm
MAZAS	[F] Giant Alloy, CenterLock, 12mm thru-axle [R] Giant Alloy, 3 pawl 30t driver, CenterLock, 12mm thru-axle
RAYOS	SAPIM Sprint
NEUMÁTICOS	CADEX Aero, tubeless, 700x25c (26.5mm), folding
EXTRAS	bento box top tube storage, hydration kit, computer mount, tubeless prepared, 30mm max tire size
LIMITS	
MAX TIRE CLEARANCE	30mm

Precio: \$189,990.00

GEOMETRÍA

CUADRO	XXS	XS	S
Longitud de la Base del Poste de Asiento (mm)	440	477	508
Ángulo de la Base del Poste de Asiento	77.0°	77.0°	77.0°
Longitud del Tubo Superior (mm)	493	510	530
Longitud del Telescopio (mm)	65	85	105
Ángulo del Telescopio	71.0°	72.0°	73.0°
Rake (mm)	40	40	40
Trail (mm)	79	69	63
Distancia entre Ejes (mm)	969	974	988
Longitud de Vaina Inferior (mm)	405	405	405
Caída del Eje de Centro (mm)	70	70	70
Stack (mm)	467	490	513
Reach (mm)	387	397	412
Altura del Tubo Superior al Suelo (mm)	733	758	786
Ancho del Manubrio (mm)	400	400	400
Tamaño de las Ruedas	700C	700C	700C
Arm Pad Stack	(TRI) 604-686 (TT) 556-640 (TRI) 629-709 (TT) 582-662 (TRI) 65		
Arm Pad Reach	(TRI) 309-383 (TT) 326-400 (TRI) 323-398 (TT) 339-414 (TRI) 34		

Todas las especificaciones están sujetas a cambios sin previo aviso.