

# AVOW ADVANCED SL



## SPECS

FRAME	
<b>SIZES</b>	XXS, XS, S, M
<b>COLOURS</b>	Carbon
<b>FRAME</b>	Advanced SL-grade composite, 12x142mm thru-axle, disc
<b>FORK</b>	Advanced SL-grade composite, full-composite steerer, 12x100mm, disc
<b>SHOCK</b>	N/A
COMPONENTS	
<b>HANDLEBAR</b>	AeroDrive base bar with Sync armrest set, 10- and 15-degree extension wedge
<b>GRIPS</b>	Liv Stratus Lite 2.0
<b>STEM</b>	AeroDrive integrated stem
<b>SEATPOST</b>	Liv Avow Composite
<b>SADDLE</b>	Liv Contact SL Tri
<b>ARM REST KIT</b>	Sync armrest set
DRIVETRAIN	
<b>SHIFTERS</b>	SRAM eTap Clics, extension mounted SRAM eTap Blips, basebar mounted
<b>FRONT DERAILLEUR</b>	SRAM Rival eTap AXS
<b>REAR DERAILLEUR</b>	SRAM Rival eTap AXS
<b>BRAKES</b>	SRAM Rival eTap hydraulic, SRAM PaceLine rotors [F]160mm, [R]140mm
<b>BRAKE LEVERS</b>	SRAM S-900 Aero hydraulic
<b>CASSETTE</b>	SRAM Rival XG-1250, 12-speed, 10x36
<b>CHAIN</b>	SRAM Rival D1
<b>CRANKSET</b>	SRAM Rival, 35/48 with power meter XXS: 160mm, XS: 160mm, S: 160mm, M: 165mm, L: 165mm
<b>BOTTOM BRACKET</b>	SRAM DUB, press fit

WHEELS	
<b>RIMS</b>	Giant SLR 2 50 WheelSystem, [F]50mm, [R]50mm
<b>HUBS</b>	[F] Giant Alloy, CenterLock, 12mm thru-axle [R] Giant Alloy, 3 pawl 30t driver, CenterLock, 12mm thru-axle
<b>SPOKES</b>	SAPIM Sprint
<b>TIRES</b>	CADEX Aero, tubeless, 700x25c (26.5mm), folding
<b>EXTRAS</b>	bento box top tube storage, hydration kit, computer mount, tubeless prepared, 30mm max tire size
LIMITS	
<b>MAX TIRE CLEARANCE</b>	30mm

**Suggested Retail Price (CDN): \$9,999.00**

## FRAME GEOMETRY

FRAME	XXS	XS	S
Seat Tube Length (mm)	440	477	508
Seat Tube Angle	77.0°	77.0°	77.0°
Top Tube Length (mm)	493	510	530
Head Tube Length (mm)	65	85	105
Head Tube Angle	71.0°	72.0°	73.0°
Fork Rake (mm)	40	40	40
Trail (mm)	79	69	63
Wheelbase (mm)	969	974	988
Chain Stay Length (mm)	405	405	405
Bottom Bracket Drop (mm)	70	70	70
Stack (mm)	467	490	513
Reach (mm)	387	397	412
Stand Over Height (mm)	733	758	786
Handlebar Width (mm)	400	400	400
Wheel Size	700C	700C	700C
Arm Pad Stack	(TRI) 604-686   (TT) 556-640	(TRI) 629-709   (TT) 582-662	(TRI) 653-733   (TT) 605-686
Arm Pad Reach	(TRI) 309-383   (TT) 326-400	(TRI) 323-398   (TT) 339-414	(TRI) 340-415   (TT) 355-431

*All prices and specifications are subject to change without notice.*