

# AVOW ADVANCED SL



## SPECIFIKACIJE

| OKVIR               |   |
|---------------------|---|
| VELIČINE            | XXS, XS, S, M   |
| BOJE                | Carbon  |
| OKVIR               | Advanced SL-grade composite, 12x142mm thru-axle, disc   |
| VILICA              | Advanced SL-grade composite, full-composite steerer, 12x100mm, disc                                     |
| AMORTIZER           | N/A   |
| KOMPONENTE          |   |
| VOLAN               | AeroDrive base bar with Sync armrest set, 10- and 15-degree extension wedge                             |
| GRIPS               | Liv Stratus Lite 2.0  |
| LULA VOLANA         | AeroDrive integrated stem   |
| CIJEV SJEDALA       | Liv Avow Composite  |
| SJEDALO             | Liv Contact SL Tri  |
| ARM REST KIT        | Sync armrest set  |
| POGON               |   |
| RUČICE MJENJAČA     | SRAM eTap Clics, extension mountedSRAM eTap Blips, basebar mounted                                      |
| PREDNJI MJENJAČ     | SRAM Rival eTap AXS   |
| STRAŽNJI MJENJAČ    | SRAM Rival eTap AXS   |
| KOČNICE             | SRAM Rival eTap hydraulic, SRAM PacerLine rotors [F]160mm, [R]140mm                                     |
| RUČICE KOČNICA      | SRAM S-900 Aero hydraulic   |
| KAZETA              | SRAM Rival XG-1250, 12-speed, 10x36   |
| LANAC               | SRAM Rival D1   |
| POGON               | SRAM Rival, 35/48 with Giant Power Halo power meter XXS: 160mm, XS: 160mm, S: 160mm, M: 165mm, L: 165mm |
| OSOVINA POGONA (BB) | SRAM DUB, press fit   |

| KOTAČI             |  |
|--------------------|--|
| OBRUČI             | Giant SLR 2 50 WheelSystem, [F]50mm, [R]50mm   |
| NABE               | [F] Giant Alloy, CenterLock, 12mm thru-axle [R] Giant Alloy, 3 pawl 30t driver, CenterLock, 12mm thru-axle |
| ŽBICE              | SAPIM Sprint   |
| GUME               | CADEX Aero, tubeless, 700x25c (26.5mm), folding  |
| DODACI             | bento box top tube storage, hydration kit, computer mount, tubeless prepared, 30mm max tire size           |
| LIMITS             |  |
| MAX TIRE CLEARANCE | 30mm   |

## GEOMETRIJA

| OKVIR  | XXS  | XS    |
|--|--|-------|
| Dužina cijevi sjedala (mm)   | 440  | 477   |
| Kut cijevi sjedala   | 77,0°                                      | 77,0° |
| Dužina gornje cijevi (mm)  | 493  | 510   |
| Dužina prednje cijevi (mm)   | 65   | 85    |
| Kut vilice   | 71,0°                                      | 72,0° |
| Zakrivljenost vilice (offset) (mm)                                 | 40   | 40    |
| Staza (mm)   | 79   | 69    |
| Međuosovinski razmak kotača (mm)                                   | 969  | 974   |
| Dužina od osovine pogona do osovine zadnjeg kotača (CS) (mm)       | 405  | 405   |
| Položaj osovine pogona (mm)  | 70   | 70    |
| Vertikalna dužina od osovine pogona do glave okvira (stack) (mm)   | 467  | 490   |
| Horizontalna dužina od osovine pogona do glave okvira (reach) (mm) | 387  | 397   |
| Prekoračna visina (mm)   | 733  | 758   |
| Širina volana (mm)   | 400  | 400   |
| Veličina kotača  | 700C                                       | 700C  |
| Arm Pad Stack  | (TRI) 604-686   (TT) 556-640 (TRI) 629-709 |       |
| Arm Pad Reach  | (TRI) 309-383   (TT) 326-400 (TRI) 323-398 |       |

Sve navedene specifikacije podložne su promjeni bez prethodne najave.