

AVOW ADVANCED SL



SPECS

RAMME	
STØRRELSE	XXS, XS, S, M
FARGE	Carbon
RAMME	Advanced SL-grade composite, 12x142mm thru-axle, disc
GAFFEL	Advanced SL-grade composite, full-composite steerer, 12x100mm, disc
DEMPER	N/A
KOMPONENTER	
STYRE	AeroDrive base bar with Sync armrest set, 10- and 15-degree extension wedge
GRIPS	Liv Stratus Lite 2.0
STYRSTEM	AeroDrive integrated stem
SETEPINNE	Liv Avow Composite
SADEL	Liv Contact SL Tri
ARM REST KIT	Sync armrest set
DRIVVERK	
GIRHENDLER	SRAM eTap Clics, extension mountedSRAM eTap Blips, basebar mounted
FRONTGIR	SRAM Rival eTap AXS
BAKGIR	SRAM Rival eTap AXS
BREMSER	SRAM Rival eTap hydraulic, SRAM PaceLine rotors [F]160mm, [R]140mm
BREMSEHENDLER	SRAM S-900 Aero hydraulic
KASSETT	SRAM Rival XG-1250, 12-speed, 10x36
KJEDE	SRAM Rival D1
KRANK	SRAM Rival, 35/48 with Giant Power Halo power meter XXS: 160mm, XS: 160mm, S: 160mm, M: 165mm, L: 165mm
BOTTOM BRACKET	SRAM DUB, press fit

HJUL	
FELG	Giant SLR 2 50 WheelSystem, [F]50mm, [R]50mm
NAV	[F] Giant Alloy, CenterLock, 12mm thru-axle [R] Giant Alloy, 3 pawl 30t driver, CenterLock, 12mm thru-axle
EIKE	SAPIM Sprint
DEKK	CADEX Aero, tubeless, 700x25c (26.5mm), folding
EXTRAS	bento box top tube storage, hydration kit, computer mount, tubeless prepared, 30mm max tire size
LIMITS	
MAX TIRE CLEARANCE	30mm

GEOMETRI

RAMME	XXS	XS	S
Seat Tube Length (mm)	440	477	508
Seat Tube Angle	77,0°	77,0°	77,0°
Top Tube Length (mm)	493	510	530
Head Tube Length (mm)	65	85	105
Head Tube Angle	71,0°	72,0°	73,0°
Fork Rake (mm)	40	40	40
Trail (mm)	79	69	63
Wheelbase (mm)	969	974	988
Chain Stay Length (mm)	405	405	405
Bottom Bracket Drop (mm)	70	70	70
Stack (mm)	467	490	513
Reach (mm)	387	397	412
Stand Over Height (mm)	733	758	786
Handlebar Width (mm)	400	400	400
Wheel Size	700C	700C	700C
Arm Pad Stack	(TRI) 604-686 (TT) 556-640	(TRI) 629-709 (TT) 582-662	(TRI) 653-733 (TT) 605-688
Arm Pad Reach	(TRI) 309-383 (TT) 326-400	(TRI) 323-398 (TT) 339-414	(TRI) 340-415 (TT) 355-430

Alle spesifikasjonene kan endres uten varsel.