

AVOW ADVANCED SL



SPECS

CADRU	
MARIMI	XXS, XS, S, M
CULORI	Carbon
CADRU	Advanced SL-grade composite, 12x142mm thru-axle, disc
FURCA	Advanced SL-grade composite, full-composite steerer, 12x100mm, disc
SOC	N/A
COMPONENTE	
GHIDON	AeroDrive base bar with Sync armrest set, 10- and 15-degree extension wedge
GRIPS	Liv Stratus Lite 2.0
PIPA	AeroDrive integrated stem
TIJA SA	Liv Avow Composite
SA	Liv Contact SL Tri
ARM REST KIT	Sync armrest set
SISTEMUL DE SCHIMBARE A VITEZELOR	
MANETE SCHIMBATOR	SRAM eTap Clics, extension mountedSRAM eTap Blips, basebar mounted
SCHIMBATOR FATA	SRAM Rival eTap AXS
SCHIMBATOR SPATE	SRAM Rival eTap AXS
FRANE	SRAM Rival eTap hydraulic, SRAM PaceLine rotors [F]160mm, [R]140mm
MANETE FRANA	SRAM S-900 Aero hydraulic
PINIOANE	SRAM Rival XG-1250, 12-speed, 10x36
LANT	SRAM Rival D1
ANGRENAJ	SRAM Rival, 35/48 with Giant Power Halo power meter XXS: 160mm, XS: 160mm, S: 160mm, M: 165mm, L: 165mm
BOTTOM BRACKET	SRAM DUB, press fit

ROTI	
JANTE	Giant SLR 2 50 WheelSystem, [F]50mm, [R]50mm
BUTUCI	[F] Giant Alloy, CenterLock, 12mm thru-axle [R] Giant Alloy, 3 pawl 30t driver, CenterLock, 12mm thru-axle
SPITE	SAPIM Sprint
ANVELOPE	CADEX Aero, tubeless, 700x25c (26.5mm), folding
EXTRAS	bento box top tube storage, hydration kit, computer mount, tubeless prepared, 30mm max tire size
LIMITS	
MAX TIRE CLEARANCE	30mm

GEOMETRIE

CADRU	XXS	XS	S
Seat Tube Length (mm)	440	477	508
Seat Tube Angle	77,0°	77,0°	77,0°
Top Tube Length (mm)	493	510	530
Head Tube Length (mm)	65	85	105
Head Tube Angle	71,0°	72,0°	73,0°
Fork Rake (mm)	40	40	40
Trail (mm)	79	69	63
Wheelbase (mm)	969	974	988
Chain Stay Length (mm)	405	405	405
Bottom Bracket Drop (mm)	70	70	70
Stack (mm)	467	490	513
Reach (mm)	387	397	412
Stand Over Height (mm)	733	758	786
Handlebar Width (mm)	400	400	400
Wheel Size	700C	700C	700C
Arm Pad Stack	(TRI) 604-686 (TT) 556-640	(TRI) 629-709 (TT) 582-662	(TRI) 653-733 (TT) 605-685
Arm Pad Reach	(TRI) 309-383 (TT) 326-400	(TRI) 323-398 (TT) 339-414	(TRI) 340-415 (TT) 355-430

Toate specificatiile enumerate se pot schimba fara notificare prealabila.