

AVOW ADVANCED SL



SPECS

FRAME	
SIZES	XXS, XS, S, M
COLORS	Carbon
FRAME	Advanced SL-grade composite, 12x142mm thru-axle, disc
FORK	Advanced SL-grade composite, full-composite steerer, 12x100mm, disc
SHOCK	N/A
COMPONENTS	
HANDLEBAR	AeroDrive base bar with Sync armrest set, 10- and 15-degree extension wedge
GRIPS	Liv Stratus Lite 2.0
STEM	AeroDrive integrated stem
SEATPOST	Liv Avow Composite
SADDLE	Liv Contact SL Tri
ARM REST KIT	Sync armrest set
DRIVETRAIN	
SHIFTERS	SRAM eTap Clics, extension mountedSRAM eTap Blips, basebar mounted
FRONT DERAILLEUR	SRAM Rival eTap AXS
REAR DERAILLEUR	SRAM Rival eTap AXS
BRAKES	SRAM Rival eTap hydraulic, SRAM PacerLine rotors [F]160mm, [R]140mm
BRAKE LEVERS	SRAM S-900 Aero hydraulic
CASSETTE	SRAM Rival XG-1250, 12-speed, 10x36
CHAIN	SRAM Rival D1
CRANKSET	SRAM Rival, 35/48 with Giant Power Halo power meter XXS: 160mm, XS: 160mm, S: 160mm, M: 165mm, L: 165mm
BOTTOM BRACKET	SRAM DUB, press fit

WHEELS	
RIMS	Giant SLR 2 50 WheelSystem, [F]50mm, [R]50mm
HUBS	[F] Giant Alloy, CenterLock, 12mm thru-axle [R] Giant Alloy, 3 pawl 30t driver, CenterLock, 12mm thru-axle
SPOKES	SAPIM Sprint
TIRES	CADEX Aero, tubeless, 700x25c (26.5mm), folding
EXTRAS	bento box top tube storage, hydration kit, computer mount, tubeless prepared, 30mm max tire size
LIMITS	
MAX TIRE CLEARANCE	30mm

GEOMETRY

FRAME	XXS	XS	S
Seat Tube Length (mm)	440	477	508
Seat Tube Angle	77.0°	77.0°	77.0°
Top Tube Length (mm)	493	510	530
Head Tube Length (mm)	65	85	105
Head Tube Angle	71.0°	72.0°	73.0°
Fork Rake (mm)	40	40	40
Trail (mm)	79	69	63
Wheelbase (mm)	969	974	988
Chain Stay Length (mm)	405	405	405
Bottom Bracket Drop (mm)	70	70	70
Stack (mm)	467	490	513
Reach (mm)	387	397	412
Stand Over Height (mm)	733	758	786
Handlebar Width (mm)	400	400	400
Wheel Size	700C	700C	700C
Arm Pad Stack	(TRI) 604-686 (TT) 556-640	(TRI) 629-709 (TT) 582-662	(TRI) 653-733 (TT) 605-685
Arm Pad Reach	(TRI) 309-383 (TT) 326-400	(TRI) 323-398 (TT) 339-414	(TRI) 340-415 (TT) 355-430

All specifications listed are subject to change without notice.