

AVOW ADVANCED SL TRI FRAMESET



СПЕЦИФИКАЦИИ

РАМКА	
РАЗМЕР	XXS, XS, S, M
ЦВЯТ	Ultra Navy
РАМКА	Advanced SL-grade composite, 12x142mm thru-axle, disc
ВИЛКА	Advanced SL-grade composite, full-composite steerer, 12x100mm, disc
КОМПОНЕНТИ	
КОРМИЛО	AeroDrive base bar with Sync armrest set, 10- and 15-degree extension wedge
ЛАПА	AeroDrive integrated stem
КОЛЧЕ ЗА СЕДАЛКА	Liv Avow Composite
ARM REST KIT	Sync armrest set

КАПЛИ	
ЭКСТРИ	bento box top tube storage, hydration kit, computer mount, 30mm max tire size
ЛИМИТИ	
MAX TIRE CLEARANCE	30mm

ГЕОМЕТРИЯ

РАМКА	XXS	XS	S
Seat Tube Length (mm)	440	477	508
Seat Tube Angle	77,0°	77,0°	77,0°
Top Tube Length (mm)	493	510	530
Head Tube Length (mm)	65	85	105
Head Tube Angle	71,0°	72,0°	73,0°
Fork Rake (mm)	40	40	40
Trail (mm)	79	69	63
Wheelbase (mm)	969	974	988
Chain Stay Length (mm)	405	405	405
Bottom Bracket Drop (mm)	70	70	70
Stack (mm)	467	490	513
Обсер (mm)	387	397	412
Stand Over Height (mm)	733	758	786
Ширина на Кормило (mm)	400	400	400
Размер на Каплите	700C	700C	700C
Arm Pad Stack	(TRI) 604-686 (TT) 556-640	(TRI) 629-709 (TT) 582-662	(TRI) 653-733 (TT) 605-686
Arm Pad Reach	(TRI) 309-383 (TT) 326-400	(TRI) 323-398 (TT) 339-414	(TRI) 340-415 (TT) 355-430

All specifications listed are subject to change without notice.