

# AVOW ADVANCED SL TRI FRAMESET



## SPECIFIKATIONER

RAMME	
STØRRELSER	XXS, XS, S, M
FARVER	Ultra Navy
RAMME	Advanced SL-grade composite, 12x142mm thru-axle, disc
FORGAFFEL	Advanced SL-grade composite, full-composite steerer, 12x100mm, disc
KOMPONENTER	
STYR	AeroDrive base bar with Sync armrest set, 10- and 15-degree extension wedge
FREMPIND	AeroDrive integrated stem
SADELPIND	Liv Avow Composite
ARM REST SÆT	Sync armrest set

HJUL	
EKSTRA	bento box top tube storage, hydration kit, computer mount, 30mm max tire size
GRÆNSER	
MAX DÆKSTØRRELSE	30mm

Pris: 33.899,00 kr.

## GEOMETRI

RAMME	XS	S	M
Sadelrørslængde (mm)	477	508	538
Sadelrørsvinkel	77,0°	77,0°	77,0°
Overrørslængde (mm)	510	530	554
Kronrørslængde (mm)	85	105	125
Kronrørsvinkel	72,0°	73,0°	73,0°
Forgaffel fremspring (rake) (mm)	40	40	40
Sti (mm)	69	63	63
Akselafstand (mm)	974	988	1013
Kædestagslængde (mm)	405	405	405
Krankboks drop (mm)	70	70	70
Stack (mm)	490	513	532
Reach (mm)	397	412	432
Skridthøjde (mm)	758	786	814
Styrbredde (mm)	400	400	400
Hjulstørrelse	700C	700C	700C
Armstøtte stack	(TRI) 629-709   (TT) 582-662 (TRI) 653-733   (TT) 605-685 (TRI) 672-752   (TT) 625-707		
Armstøtte reach	(TRI) 323-398   (TT) 339-414 (TRI) 340-415   (TT) 355-430 (TRI) 360-435   (TT) 371-446		

Alle de anførte specifikationer kan ændres uden varsel.