

AVOW ADVANCED SL TRI FRAMESET



SPECS

ΣΚΕΛΕΤΟΣ	
ΜΕΓΕΘΗ	XXS, XS, S, M
ΧΡΩΜΑΤΑ	Ultra Navy
ΣΚΕΛΕΤΟΣ	Advanced SL-grade composite, 12x142mm thru-axle, disc
ΠΙΡΟΥΝΙ	Advanced SL-grade composite, full-composite steerer, 12x100mm, disc
ΕΞΑΡΤΗΜΑΤΑ	
ΤΙΜΟΝΙ	AeroDrive base bar with Sync armrest set, 10- and 15-degree extension wedge
ΛΑΙΜΟΣ ΤΙΜΟΝΙΟΥ	AeroDrive integrated stem
ΛΑΙΜΟΣ ΣΤΕΛΛΑΣ	Liv Avow Composite
ARM REST KIT	Sync armrest set

WHEELS	
EXTRAS	bento box top tube storage, hydration kit, computer mount, 30mm max tire size
LIMITS	
MAX TIRE CLEARANCE	30mm

ΓΕΩΜΕΤΡΙΑ

ΣΚΕΛΕΤΟΣ	XXS	XS	S
Seat Tube Length (mm)	440	477	508
Seat Tube Angle	77,0°	77,0°	77,0°
Top Tube Length (mm)	493	510	530
Head Tube Length (mm)	65	85	105
Head Tube Angle	71,0°	72,0°	73,0°
Fork Rake (mm)	40	40	40
Trail (mm)	79	69	63
Wheelbase (mm)	969	974	988
Chain Stay Length (mm)	405	405	405
Bottom Bracket Drop (mm)	70	70	70
Stack (mm)	467	490	513
Reach (mm)	387	397	412
Stand Over Height (mm)	733	758	786
Handlebar Width (mm)	400	400	400
Wheel Size	700C	700C	700C
Arm Pad Stack	(TRI) 604-686 (TT) 556-640	(TRI) 629-709 (TT) 582-662	(TRI) 653-733 (TT) 605-686
Arm Pad Reach	(TRI) 309-383 (TT) 326-400	(TRI) 323-398 (TT) 339-414	(TRI) 340-415 (TT) 355-430

Όλες οι προδιαγραφές είναι δυνατό να αλλάξουν χωρίς πρότερη ειδοποίηση