

AVOW ADVANCED SL TRI FRAMESET



SPECS

FRAME	
SIZES	XXS, XS, S, M
COLORS	Ultra Navy
FRAME	Advanced SL-grade composite, 12x142mm thru-axle, disc
FORK	Advanced SL-grade composite, full-composite steerer, 12x100mm, disc
COMPONENTS	
HANDLEBAR	AeroDrive base bar with Sync armrest set, 10- and 15-degree extension wedge
STEM	AeroDrive integrated stem
SEATPOST	Liv Avow Composite
ARM REST KIT	Sync armrest set

WHEELS	
EXTRAS	bento box top tube storage, hydration kit, computer mount, 30mm max tire size
LIMITS	
MAX TIRE CLEARANCE	30mm

Price: ₹ 4,299.00

GEOMETRY

FRAME	XXS	XS	S
Seat Tube Length (mm)	440	477	508
Seat Tube Angle	77.0°	77.0°	77.0°
Top Tube Length (mm)	493	510	530
Head Tube Length (mm)	65	85	105
Head Tube Angle	71.0°	72.0°	73.0°
Fork Rake (mm)	40	40	40
Trail (mm)	79	69	63
Wheelbase (mm)	969	974	988
Chain Stay Length (mm)	405	405	405
Bottom Bracket Drop (mm)	70	70	70
Stack (mm)	467	490	513
Reach (mm)	387	397	412
Stand Over Height (mm)	733	758	786
Handlebar Width (mm)	400	400	400
Wheel Size	700C	700C	700C
Arm Pad Stack	(TRI) 604-686 (TT) 556-640	(TRI) 629-709 (TT) 582-662	(TRI) 653-733 (TT) 605-688
Arm Pad Reach	(TRI) 309-383 (TT) 326-400	(TRI) 323-398 (TT) 339-414	(TRI) 340-415 (TT) 355-430

The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city / country.