

# AVOW ADVANCED SL TRI FRAMESET



## ESPECIFICACIONES

CUADRO	
TALLAS	XXS, XS, S, M
COLORES	Ultra Navy
CUADRO	Advanced SL-grade composite, 12x142mm thru-axle, disc
TIJERA	Advanced SL-grade composite, full-composite steerer, 12x100mm, disc
COMPONENTES	
MANUBRIO	AeroDrive base bar with Sync armrest set, 10- and 15-degree extension wedge
POTENCIA	AeroDrive integrated stem
POSTE DE ASIENTO	Liv Avow Composite
ARM REST KIT	Sync armrest set

RUEDAS	
EXTRAS	bento box top tube storage, hydration kit, computer mount, 30mm max tire size
LIMITS	
MAX TIRE CLEARANCE	30mm

**Precio: \$115,000.00**

## GEOMETRÍA

CUADRO	XXS	XS	S
Longitud de la Base del Poste de Asiento (mm)	440	477	508
Ángulo de la Base del Poste de Asiento	77.0°	77.0°	77.0°
Longitud del Tubo Superior (mm)	493	510	530
Longitud del Telescopio (mm)	65	85	105
Ángulo del Telescopio	71.0°	72.0°	73.0°
Rake (mm)	40	40	40
Trail (mm)	79	69	63
Distancia entre Ejes (mm)	969	974	988
Longitud de Vaina Inferior (mm)	405	405	405
Caída del Eje de Centro (mm)	70	70	70
Stack (mm)	467	490	513
Reach (mm)	387	397	412
Altura del Tubo Superior al Suelo (mm)	733	758	786
Ancho del Manubrio (mm)	400	400	400
Tamaño de las Ruedas	700C	700C	700C
Arm Pad Stack	(TRI) 604-686   (TT) 556-640	(TRI) 629-709   (TT) 582-662	(TRI) 65
Arm Pad Reach	(TRI) 309-383   (TT) 326-400	(TRI) 323-398   (TT) 339-414	(TRI) 34

Todas las especificaciones están sujetas a cambios sin previo aviso.