

AVOW ADVANCED SL TRI FRAMESET



SPECIFIKACIJE

OKVIR	
VELIČINE	XXS, XS, S, M
BOJE	Ultra Navy
OKVIR	Advanced SL-grade composite, 12x142mm thru-axle, disc
VILICA	Advanced SL-grade composite, full-composite steerer, 12x100mm, disc
KOMPONENTE	
VOLAN	AeroDrive base bar with Sync armrest set, 10- and 15-degree extension wedge
LULA VOLANA	AeroDrive integrated stem
CIJEV SJEDALA	Liv Avow Composite
ARM REST KIT	Sync armrest set

KOTAČI	
DODACI	bento box top tube storage, hydration kit, computer mount, 30mm max tire size
LIMITS	
MAX TIRE CLEARANCE	30mm

GEOMETRIJA

OKVIR	XXS	XS
Dužina cijevi sjedala (mm)	440	477
Kut cijevi sjedala	77,0°	77,0°
Dužina gornje cijevi (mm)	493	510
Dužina prednje cijevi (mm)	65	85
Kut vilice	71,0°	72,0°
Zakrivljenost vilice (offset) (mm)	40	40
Staza (mm)	79	69
Međuosovinski razmak kotača (mm)	969	974
Dužina od osovine pogona do osovine zadnjeg kotača (CS) (mm)	405	405
Položaj osovine pogona (mm)	70	70
Vertikalna dužina od osovine pogona do glave okvira (stack) (mm)	467	490
Horizontalna dužina od osovine pogona do glave okvira (reach) (mm)	387	397
Prekoračna visina (mm)	733	758
Širina volana (mm)	400	400
Veličina kotača	700C	700C
Arm Pad Stack	(TRI) 604-686 (TT) 556-640	(TRI) 629-709
Arm Pad Reach	(TRI) 309-383 (TT) 326-400	(TRI) 323-398

Sve navedene specifikacije podložne su promjeni bez prethodne najave.