

# AVOW ADVANCED SL TRI FRAMESET



## SPECIFICATIES

FRAME	
MATEN	XXS, XS, S, M
KLEUREN	Ultra Navy
FRAME	Advanced SL-grade composite, 12x142mm thru-axle, disc
VOORVORK	Advanced SL-grade composite, full-composite steerer, 12x100mm, disc
ONDERDELEN	
STUUR	AeroDrive base bar with Sync armrest set, 10- and 15-degree extension wedge
STUURPEN	AeroDrive integrated stem
ZADELPEN	Liv Avow Composite
ARMSTEUNSET	Sync armrest set

WIELSET	
EXTRA'S	bento box top tube storage, hydration kit, computer mount, 30mm max tire size
LIMITS	
MAXIMALE BANDENVRIJHEID	30mm

Adviesprijs: € 4.299,00

## GEOMETRIE

FRAME	XS	S	M
Zitbuis Lengte (mm)	477	508	538
Zitbuis Hoek	77,0°	77,0°	77,0°
Frame Lengte (horizontaal) (mm)	510	530	554
Balhoofdbuis Lengte (mm)	85	105	125
Balhoofdbuis Hoek	72,0°	73,0°	73,0°
Vork Sprong (mm)	40	40	40
Naloop (mm)	69	63	63
Wielbasis (mm)	974	988	1013
Liggende achtervork lengte (mm)	405	405	405
Bottom Bracket Drop (mm)	70	70	70
Stack (mm)	490	513	532
Reach (mm)	397	412	432
Stand Over Height (mm)	758	786	814
Stuur breedte (mm)	400	400	400
Wielmaat	700C	700C	700C
Arm Pad Stack	(TRI) 629-709   (TT) 582-662 (TRI) 653-733   (TT) 605-685 (TRI) 672-752   (TT) 6		
Arm Pad Reach	(TRI) 323-398   (TT) 339-414 (TRI) 340-415   (TT) 355-430 (TRI) 360-435   (TT) 3		

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder vooraankondiging wijzigen.