

AVOW ADVANCED SL TRI FRAMESET



ŠPECIFIKÁCIE

RÁM	
VELKOSTI	XXS, XS, S, M
FARBY	Ultra Navy
RÁM	Advanced SL-grade composite, 12x142mm thru-axle, disc
VIDLICA	Advanced SL-grade composite, full-composite steerer, 12x100mm, disc
KOMPONENTY	
RIADIDLÁ	AeroDrive base bar with Sync armrest set, 10- and 15-degree extension wedge
PREDSTAVEC	AeroDrive integrated stem
SEDLOVKA	Liv Avow Composite
ARM REST KIT	Sync armrest set

KOLESÁ	
DOPLNKY	bento box top tube storage, hydration kit, computer mount, 30mm max tire size
LIMITY	
MAXIMÁLNA ŠÍRKA PNEUMATÍK	30mm

Cena: 4 199 €

GEOMETRIA

RÁM	XXS	XS	S
Dĺžka sedlovej trubky (mm)	440	477	508
Uhol sedlovej trubky	77,0°	77,0°	77,0°
Dĺžka hornej rámovej trubky (mm)	493	510	530
Dĺžka hlavovej trubky (mm)	65	85	105
Uhol hlavovej trubky	71,0°	72,0°	73,0°
Offset vidlice (mm)	40	40	40
Trail (mm)	79	69	63
Rázvor (mm)	969	974	988
Dĺžka zadnej stavby (mm)	405	405	405
Rozdiel zadnej voči stredovej osi - BB DROP (mm)	70	70	70
Stack - výška riadenia (mm)	467	490	513
Reach (mm)	387	397	412
Výška rámu od zeme (mm)	733	758	786
Šírka riaditok (mm)	400	400	400
Rozmer kolies	700C	700C	700C
Arm Pad Stack	(TRI) 604-686 (TT) 556-640	(TRI) 629-709 (TT) 582-662	(TRI) 654-734 (TT) 604-686
Arm Pad Reach	(TRI) 309-383 (TT) 326-400	(TRI) 323-398 (TT) 339-414	(TRI) 337-411 (TT) 354-431

Všetky ceny a špecifikácie sa môžu zmeniť bez predchádzajúceho upozornenia.