

# AVOW ADVANCED SL



## 產品規格

車架	
尺寸	XXS, XS, S,
顏色	Carbon 紫紅
車架	Advanced SL-grade composite, 12x142mm thru-axle, disc
前叉	Advanced SL-grade composite, full-composite steerer, 12x100mm, disc
避震器	N/A
COMPONENTS	
車把手	AeroDrive base bar with Sync armrest set, 10- and 15-degree extension wedge
把手帶/套	Liv Stratus Lite 2.0
豎桿	AeroDrive integrated stem
座桿	Liv Avow Composite
坐墊	Liv Contact SL Tri
ARM REST KIT	Sync armrest set
DRIVETRAIN	
變速把手	SRAM eTap Clicks, extension mounted SRAM eTap Blips, basebar mounted
前變速器	SRAM Rival eTap AXS
後變速器	SRAM Rival eTap AXS
煞車系統	SRAM Rival eTap hydraulic, SRAM PaceLine rotors [F]160mm, [R]140mm
煞車把手	SRAM S-900 Aero hydraulic
飛輪	SRAM Rival XG-1250, 12-speed, 10x36
鍊條	SRAM Rival E1
大齒盤	SRAM Rival, 35/48 with power meter XXS: 160mm, XS: 160mm, S: 160mm,
BOTTOM BRACKET (B B)	SRAM DUB, press fit

輪組	
輪圈	Giant SLR 2 50 WheelSystem, [F]50mm, [R]50mm
花鼓	[F] Giant Alloy, CenterLock, 12mm thru-axle [R] Giant Alloy, 3 pawl 30t driver, CenterLock, 12mm thru-axle
輻條	SAPIM Sprint
外胎	CADEX Aero, tubeless, 700x25c (26.5mm), folding
其他	bento box top tube storage, hydration kit, computer mount, tubeless prepared, 30mm max tire size
LIMITS	
MAX TIRE CLEARANCE	30mm

Price: NT\$198,000

## 車架幾何

車架	XXS	XS	S	M
座(立)管長 (mm)	440	477	508	538
座(立)管角度	77.0°	77.0°	77.0°	77.0°
上管長度 (mm)	493	510	530	554
頭管長度 (mm)	65	85	105	125
頭管角度	71.0°	72.0°	73.0°	73.0°
前叉 (mm)	40	40	40	40
Trail (mm)	79	69	63	63
前後輪距 (mm)	969	974	988	1013
後下叉長度 (mm)	405	405	405	405
五通下降高度 (mm)	70	70	70	70
頭碗至五通高度 (mm)	467	490	513	532
頭碗至五通長度 (mm)	387	397	412	432
上管至地面高度 (mm)	733	758	786	814
把手寬 (mm)	400	400	400	400
輪組尺寸	700C	700C	700C	700C
肘靠上移範圍	(TRI) 604-686   (TT) 556-640 (TRI) 629-709   (TT) 582-662 (TRI) 653-733   (TT) 605-685 (TRI)			
肘靠前伸範圍	(TRI) 309-383   (TT) 326-400 (TRI) 323-398   (TT) 339-414 (TRI) 340-415   (TT) 355-430 (TRI)			

\* 捷安特公司對本網站所刊載之產品資料保留修改權利，恕不另行通知(包括有關設備、規格、型號、重量、顏色和材料等)，請以實際產品為主。