BELIV AR 0



SPECS

FRAME	
SIZES	XS, S, M
COLOURS	Camel Silk
FRAME	ALUXX SL-grade aluminium, UDH, 12x142mm thru-axle, disc
FORK	Advanced-grade composite, full-composite OverDrive steerer, 12x100mm thru-axle, disc
COMPONENTS	
HANDLEBAR	Liv Contact XS:35/38cm, S:37/40cm, M:39/42cm
GRIPS	Giant
STEM	Giant Contact AeroLight XS:70mm, S:80mm, M:90mm
SEATPOST	Giant D-Fuse, composite, 14mm offset
SADDLE	Liv Approach
PEDALS	N/A
DRIVETRAIN	
SHIFTERS	Shimano 105
FRONT DERAILLEUR	Shimano 105
REAR DERAILLEUR	Shimano 105
BRAKES	Shimano 105 hydraulic, Giant MPH rotors [F]160mm, [R]160mm
BRAKE LEVERS	Shimano 105 hydraulic
CASSETTE	Shimano 105, 12-speed, 11x36
CHAIN	KMC X12L-1
CRANKSET	Shimano 105, 34/50 XS:165mm, S:165mm, M:170mm
BOTTOM BRACKET	Shimano, threaded

WHEELS	
RIMS	Giant P-AR 2 Disc wheelset, alloy [F] 23mm, [R] 23mm
HUBS	[F] Giant alloy, 6 bolt, 24H [R] Giant alloy, 6 bolt, 24H
SPOKES	Stainless, 14g
TYRES	Giant Gavia Fondo 2, tubeless, 700x32c
EXTRAS	Tubeless prepared
LIMITS	
MAX TYRE CLEARANCE	43mm

Price: $2,799.00

GEOMETRY

FRAME	XS	S	M
Seat Tube Length (mm)	410	445	480
Seat Tube Angle	74.5°	74.5°	74.0°
Top Tube Length (mm)	515	525	540
Head Tube Length (mm)	118	138	158
Head Tube Angle	70.5°	71.5°	72.0°
Fork Rake (mm)	53	53	53
Trail (mm)	70	63	60
Wheelbase (mm)	999	1001	1006
Chain Stay Length (mm)	422	422	422
Bottom Bracket Drop (mm)	80	80	80
Stack (mm)	538	561	582
Reach (mm)	366	369	373
Stand Over Height (mm)	703.7	730.7	760.4
Stem Length (mm)	70	80	90
Crank Length (mm)	165	165	170
Wheel Size	700C	700C	700C

*Please note that our specifications may be impacted by running substitution changes, we highly recommend confirming the specifications of our products with your local retailer at the time of sale if purchasing in-store. *Recommended Retail Prices are subject to change without notice and may vary from store to store depending on freighting and assembly costs.*