

BELIV AR 0



SPECS

FRAME	
SIZES	XXS, XS, S, M, L
COLOURS	Camel Silk
FRAME	ALUXX SL-grade aluminum, 12x142mm thru-axle, disc
FORK	Advanced-grade composite, full-composite OverDrive steerer, 12x100mm, disc
COMPONENTS	
HANDLEBAR	Giant Contact, flare, 31.8mm XXS & XS: 350/380mm, S & M: 370/400mm, L: 390/420mm
GRIPS	Liv All Condition
STEM	Giant Contact AeroLight, -10-degree XXS: 70mm, XS: 70mm, S: 80mm, M: 90mm, L: 90mm
SEATPOST	Giant D-Fuse, composite, 14mm offset
SADDLE	Liv Approach
PEDALS	Platform pedal
DRIVETRAIN	
SHIFTERS	Shimano 105 HRD
FRONT DERAILLEUR	Shimano 105
REAR DERAILLEUR	Shimano 105
BRAKES	Shimano 105 hydraulic, Giant MPH rotors [F]160mm, [R]160mm
BRAKE LEVERS	Shimano 105
CASSETTE	Shimano 105, 12-speed, 11x36
CHAIN	KMC X12L-1
CRANKSET	Shimano 105, 34/50 XXS: 160mm, XS: 165mm, S: 165mm, M: 170mm, L: 170mm
BOTTOM BRACKET	Shimano BB-R5501

WHEELS	
RIMS	Giant P-AR 2 wheelset, alloy, [F] 23 mm, [R] 23 mm
HUBS	Giant alloy, 12mm thru-axle
SPOKES	Sapim
TIRES	Giant Gavia Fondo 2, tubeless, 700x32c (34mm)
EXTRAS	tubeless prepared, 43mm max tire size

Suggested Retail Price (CDN): \$2,499.00

FRAME GEOMETRY

FRAME	XXS	XS	S	M	L
Seat Tube Length (mm)	375	410	445	480	515
Seat Tube Angle	75.0°	74.5°	74.5°	74.0°	74.0°
Top Tube Length (mm)	502	515	525	540	555
Head Tube Length (mm)	110	118	138	158	178
Head Tube Angle	70.0°	70.5°	71.5°	72.0°	72.0°
Fork Rake (mm)	53	53	53	53	53
Trail (mm)	73	70	63	60	60
Wheelbase (mm)	994	999	1001	1006	1022
Chain Stay Length (mm)	422	422	422	422	422
Bottom Bracket Drop (mm)	80	80	80	80	80
Stack (mm)	522	538	561	582	601
Reach (mm)	362	366	369	373	383
Stand Over Height (mm)	680.3	703.7	730.7	760.4	788.7
Handlebar Width (mm)	350	350	370	370	390
Stem Length (mm)	70	70	80	90	90
Crank Length (mm)	160	165	165	170	170
Wheel Size	700C	700C	700C	700C	700C

All prices and specifications are subject to change without notice.