BELIV SL 0



SPEZIFIKATIONEN

RAHMEN & GABEL	
RAHMENGRÖSSEN	XXS, XS, S, M, L
FARBE(N)	Asphalt Green/Chrome
RAHMEN	ALUXX SL-grade aluminum, 12x142mm thru-axle, disc
GABEL	Advanced-grade composite, full-composite OverDrive steerer, 12x100mm, disc
COCKPIT	
LENKER	Giant Contact, flare, 31.8mm XXS & XS: 350/380mm, S & M: 370/400mm, L: 390/420mm
GRIFFE	Cork
VORBAU	Giant Contact AeroLight, -10-degree XXS: 80mm, XS: 80mm, S: 90mm, M: 90mm, L: 90mm
SATTELSTÜTZE	Giant D-Fuse, composite, 14mm offset
SATTEL	Liv Grit
SCHALTUNG, ANTRIEB	
SCHALTHEBEL	Shimano 105
UMWERFER	Shimano 105
SCHALTWERK	Shimano 105
BREMSEN	Shimano 105, Giant MPH rotors, [F]160mm, [R]140mm
BREMSHEBEL	Shimano 105
KASSETTE	Shimano 105, 12-speed, 11x36
KETTE	KMC X12L-1
KURBELSATZ	Shimano 105, 34/50 XXS: 160mm, XS: 165mm, S: 165mm, M: 170mm, L: 170mm
INNENLAGER	Shimano, press fit

LAUFRÄDER	
FELGEN	Giant ALP wheelset, alloy, [F] 25mm, [R] 25mm
NABEN (V/H)	Giant alloy, 12mm thru-axle
SPEICHEN	Sapim
REIFEN	Giant SR 1, 700x28c (30mm)
GRENZEN	
MAX. REIFENBREITE	32mm

UVP: 1.700,00 €

GEOMETRIEDATEN

RAHMEN & GABEL	XXS	XS	S	M	L
Sitzrohrlänge (mm)	385	405	435	465	495
Sitzwinkel	75,0°	74,5°	74,5°	74,0°	74,0°
Oberrohrlänge (mm)	500	520	525	535	550
Steuerrohrlänge (mm)	110	125	145	165	185
Lenkwinkel	69,8°	71,0°	71,0°	71,0°	72,0°
Gabelvorbiegung (mm)	50	50	50	50	50
Gabelnachlauf (mm)	75,7	67,8	67,8	67,8	61,3
Radstand (mm)	989,9	995,7	1002	1007,9	1013,9
Kettenstrebenlänge (mm)	420	420	420	420	420
Tretlagerabsenkung (mm)	75	75	75	75	75
Stack (mm)	510,1	528,6	547,6	566,5	589,3
Reach (mm)	363,3	373,4	373,1	372,6	381
Überstands-/Durchstiegshöhe (mm)	669,1	686,4	712	737	771,4
Lenkerbreite (mm)	350	350	370	370	390
Vorbaulänge (mm)	70	70	80	90	90
Kurbelarmlänge (mm)	165	165	170	170	172,5
Raddurchmesser	700C	700C	700C	700C	700C

Spezifikations-, Preis- und Farbänderungen vorbehalten.