

BELIV SL 0



SPECS

FRAME	
SIZES	XXS, XS, S, M, L
COLOURS	Asphalt Green/Chrome
FRAME	ALUXX SL-grade aluminum, 12x142mm thru-axle, disc
FORK	Advanced-grade composite, full-composite OverDrive steerer, 12x100mm, disc
COMPONENTS	
HANDLEBAR	Giant Contact, flare, 31.8mm XXS & XS: 350/380mm, S & M: 370/400mm, L: 390/420mm
GRIPS	Cork
STEM	Giant Contact AeroLight, -10-degree XXS: 80mm, XS: 80mm, S: 90mm, M: 90mm, L: 90mm
SEATPOST	Giant D-Fuse, composite, 14mm offset
SADDLE	Liv Grit
DRIVETRAIN	
SHIFTERS	Shimano 105
FRONT DERAILLEUR	Shimano 105
REAR DERAILLEUR	Shimano 105
BRAKES	Shimano 105, Giant MPH rotors, [F]160mm, [R]140mm
BRAKE LEVERS	Shimano 105
CASSETTE	Shimano 105, 12-speed, 11x36
CHAIN	KMC X12L-1
CRANKSET	Shimano 105, 34/50 XXS: 160mm, XS: 165mm, S: 165mm, M: 170mm, L: 170mm
BOTTOM BRACKET	Shimano, press fit

WHEELS	
RIMS	Giant ALP wheelset, alloy, [F] 25mm, [R] 25mm
HUBS	Giant alloy, 12mm thru-axle
SPOKES	Sapim
TIRES	Giant SR 1, 700x28c (30mm)
LIMITS	
MAX TIRE CLEARANCE	32mm

Suggested Retail Price (CDN): \$2,699.00

FRAME GEOMETRY

FRAME	XXS	XS	S
Seat Tube Length (mm)	385	405	435
Seat Tube Angle	75.0°	74.5°	74.5°
Top Tube Length (mm)	500	520	525
Head Tube Length (mm)	110	125	145
Head Tube Angle	69.8°	71.0°	71.0°
Fork Rake (mm)	50	50	50
Trail (mm)	75.7	67.8	67.8
Wheelbase (mm)	989.9	995.7	1002
Chain Stay Length (mm)	420	420	420
Bottom Bracket Drop (mm)	75	75	75
Stack (mm)	510.1	528.6	547.6
Reach (mm)	363.3	373.4	373.1
Stand Over Height (mm)	669.1	686.4	712
Handlebar Width (mm)	350	350	370
Stem Length (mm)	70	70	80
Crank Length (mm)	165	165	170
Wheel Size	700C	700C	700C

All prices and specifications are subject to change without notice.