BELIV SL 0



SPECIFICATIES

FRAME	
MATEN	XXS, XS, S, M, L
KLEUREN	Asphalt Green/Chrome
FRAME	ALUXX SL-grade aluminum, 12x142mm thru-axle, disc
VOORVORK	Advanced-grade composite, full-composite OverDrive steerer, 12x100mm, disc
ONDERDELEN	
STUUR	Giant Contact, flare, 31.8mm XXS & XS: 350/380mm, S & M: 370/400mm, L: 390/420mm
HANDVATTEN	Cork
STUURPEN	Giant Contact AeroLight, -10-degree XXS: 80mm, XS: 80mm, S: 90mm, M: 90mm, L: 90mm
ZADELPEN	Giant D-Fuse, composite, 14mm offset
ZADEL	Liv Grit
AFMONTAGE	
SHIFTERS	Shimano 105
VOORDERAILLEUR	Shimano 105
ACHTERDERAILLEUR	Shimano 105
REMMEN	Shimano 105, Giant MPH rotors, [F]160mm, [R]140mm
REMHENDELS	Shimano 105
CASSETTE	Shimano 105, 12-speed, 11x36
AANDRIJVING	KMC X12L-1
CRANKSET	Shimano 105, 34/50 XXS: 160mm, XS: 165mm, S: 165mm, M: 170mm, L: 170mm
BOTTOM BRACKET	Shimano, press fit

WIELSET	
VELGEN	Giant ALP wheelset, alloy, [F] 25mm, [R] 25mm
NAVEN	Giant alloy, 12mm thru-axle
SPAKEN	Sapim
BANDEN	Giant SR 1, 700x28c (30mm)
LIMITS	
MAX TIRE CLEARANCE	32mm

Adviesprijs: € 1.799,00

GEOMETRIE

FRAME	XS	S	M	L
Zitbuis lengte (mm)	405	435	465	495
Zitbuis hoek	74,5°	74,5°	74,0°	74,0°
Frame Lengte (horizontaal) (mm)	520	525	535	550
Balhoofdbuis Lengte (mm)	125	145	165	185
Balhoofdbuis Hoek	71,0°	71,0°	71,0°	72,0°
Vork Sprong (mm)	50	50	50	50
Naloop (mm)	67,8	67,8	67,8	61,3
Wielbasis (mm)	995,7	1002	1007,9	1013,9
Liggende achtervork lengte (mm)	420	420	420	420
Bottom Bracket Drop (mm)	75	75	75	75
Stack (mm)	528,6	547,6	566,5	589,3
Reach (mm)	373,4	373,1	372,6	381
Stand Over Height (mm)	686,4	712	737	771,4
Stuur breedte (mm)	350	370	370	390
Stuurpen Lengte (mm)	70	80	90	90
Cranklengte (mm)	165	170	170	172,5
Wielmaat	700C	700C	700C	700C

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder vooraankondiging wijzigen.