BELIV SL 0



SPECS

RAM	
STORLEKAR	XS, S, M, L
FÄRGER	Asphalt Green/Chrome
RAM	ALUXX SL-grade aluminum, 12x142mm thru-axle, disc
GAFFEL	Advanced-grade composite, full-composite OverDrive steerer, 12x100mm, disc
KOMPONENTER	
STYRE	Giant Contact, flare, 31.8mm XXS & XS: 350/380mm, S & M: 370/400mm, L: 390/420mm
GREPPAR	Cork
STAM	Giant Contact AeroLight, -10-degree XXS: 80mm, XS: 80mm, S: 90mm, M: 90mm, L: 90mm
SADELSTOLPE	Giant D-Fuse, composite, 14mm offset
SADEL	Liv Grit
DRIVLINA	
VÄXLAR	Shimano 105
FRAMVÄXEL	Shimano 105
BAKVÄXEL	Shimano 105
BROMSAR	Shimano 105, Giant MPH rotors, [F]160mm, [R]140mm
BROMSSPAKAR	Shimano 105
KASSETT	Shimano 105, 12-speed, 11x36
KEDJA	KMC X12L-1
VEVPARTI	Shimano 105, 34/50 XXS: 160mm, XS: 165mm, S: 165mm, M: 170mm, L: 170mm
BROMSREGLAGE	Shimano, press fit

HJUL	
FÄLGAR	Giant ALP wheelset, alloy, [F] 25mm, [R] 25mm
NAV	Giant alloy, 12mm thru-axle
EKRAR	Sapim
DÄCK	Giant SR 1, 700x28c (30mm)
GRÄNSER	
MAX DÄCKAVSTÅND	32mm

Price: 21 000,00 kr

GEOMETRY

RAM	XS	S	M	L
Längd sadelrör (mm)	405	435	465	495
Vinkel sadelrör	74,5°	74,5°	74,0°	74,0°
Topprörets längd (mm)	520	525	535	550
Styrhuvud Längd (mm)	125	145	165	185
Vinkel styrhuvud	71,0°	71,0°	71,0°	72,0°
Gaffelvinkel (mm)	50	50	50	50
Spår (mm)	67,8	67,8	67,8	61,3
Hjulbas (mm)	995,7	1002	1007,9	1013,9
Kedjestagslängd (mm)	420	420	420	420
Nedre fäste Drop (mm)	75	75	75	75
Stack (mm)	528,6	547,6	566,5	589,3
Reach (mm)	373,4	373,1	372,6	381
Stå över höjden (mm)	686,4	712	737	771,4
Styrets bredd (mm)	350	370	370	390
Stamlängd (mm)	70	80	90	90
Vevlängd (mm)	165	170	170	172,5
Hjulstorlek	700C	700C	700C	700C

All specifications listed are subject to change without notice.