BELIV SL 1



SPEZIFIKATIONEN

RAHMEN & GABEL	
RAHMENGRÖSSEN	XXS, XS, S, M, L
RAHMEN	ALUXX SL-grade aluminum, 12x142mm thru-axle, disc
GABEL	Advanced-grade composite, full-composite OverDrive steerer, 12x100mm, disc
COCKPIT	
LENKER	Giant Contact, 31.8mm, 7.2 degree flare XXS: 350mm, XS: 350mm, S: 370mm, M: 370mm, L: 390mm
GRIFFE	Cork (Gel) Tape VLT-001G
VORBAU	Giant Contact AeroLight, XXS: 80mm, XS: 80mm, S: 90mm, M: 90mm, L: 350mm
SATTELSTÜTZE	Giant D-Fuse, alloy, XXS: 300mm, XS: 300mm, S: 350mm, M: 350mm, L: 350mm
SATTEL	Liv Grit
SCHALTUNG, ANTRIEB	
SCHALTHEBEL	Shimano Tiagra
UMWERFER	Shimano Tiagra
SCHALTWERK	Shimano Tiagra R4000
BREMSEN	Shimano Tiagra, Giant MPH rotors, [F]160mm, [R]140mm
BREMSHEBEL	Shimano Tiagra R4000
KASSETTE	Shimano CS-RS400-11, 11X36, 11 speed
KETTE	KMC X11
KURBELSATZ	Shimano FC-R4000, 50/34
INNENLAGER	Shimano, PressFit RS500

LAUFRÄDER	
FELGEN	Giant ALP Disc
NABEN (V/H)	Giant alloy, 12mm thru-axle
SPEICHEN	stainless
REIFEN	Giant SR 1 700X28C, 60 TPI
GRENZEN	
MAX. REIFENBREITE	700x33mm

UVP: 1.500,00 €

GEOMETRIEDATEN

RAHMEN & GABEL	XXS	XS	S	M	L
Sitzrohrlänge (mm)	385	405	435	465	495
Sitzwinkel	75,0°	74,5°	74,5°	74,0°	74,0°
Oberrohrlänge (mm)	500	520	525	535	550
Steuerrohrlänge (mm)	110	125	145	165	185
Lenkwinkel	69,8°	71,0°	71,0°	71,0°	72,0°
Gabelvorbiegung (mm)	50	50	50	50	50
Gabelnachlauf (mm)	75,7	67,8	67,8	67,8	61,3
Radstand (mm)	989,9	995,7	1002	1007,9	1013,9
Kettenstrebenlänge (mm)	420	420	420	420	420
Tretlagerabsenkung (mm)	75	75	75	75	75
Stack (mm)	510,1	528,6	547,6	566,5	589,3
Reach (mm)	363,3	373,4	373,1	372,6	381
Überstands-/Durchstiegshöhe (mm)	669,1	686,4	712	737	771,4
Lenkerbreite (mm)	350	350	370	370	390
Vorbaulänge (mm)	70	70	80	90	90
Kurbelarmlänge (mm)	165	165	170	170	172,5
Raddurchmesser	700C	700C	700C	700C	700C

Spezifikations-, Preis- und Farbänderungen vorbehalten.