

BELIV SL 1



SPECS

FRAME	
SIZES	XS, S, M
COLOURS	Unicorn White
FRAME	ALUXX SL-grade aluminium, 12x142mm thru-axle, disc
FORK	Advanced-grade composite, full-composite OverDrive steerer, 12x100mm thru-axle, disc
COMPONENTS	
HANDLEBAR	Giant Contact XS:35/38cm, S:37/40cm, M:37/40cm
GRIPS	Liv
STEM	Giant Contact AeroLight XS:80mm, S:90mm, M:90mm
SEATPOST	Giant D-Fuse, composite, 14mm offset
SADDLE	Liv Grit Core
DRIVETRAIN	
SHIFTERS	Shimano Tiagra
FRONT DERAILLEUR	Shimano Tiagra
REAR DERAILLEUR	Shimano Tiagra
BRAKES	Shimano RS405 hydraulic, Giant MPH rotors [F]160mm, [R]160mm
BRAKE LEVERS	Shimano Tiagra hydraulic
CASSETTE	Shimano RS400, 11-speed, 11x36
CHAIN	KMC X11
CRANKSET	Shimano Tiagra, 34/50 XS:165mm, S:165mm, M:170mm
BOTTOM BRACKET	Shimano, press fit

WHEELS	
RIMS	Giant ALP, alloy, [F]30mm, [R]30mm
HUBS	[F] Giant alloy, 6 bolt, 12mm thru-axle [R] Giant alloy, 6 bolt, 12mm thru-axle
SPOKES	Stainless
TYRES	Giant SR 1, 700x28c
LIMITS	
MAX TYRE CLEARANCE	32mm

Price: \$2,399.00

GEOMETRY

FRAME	XS	S	M
Seat Tube Length (mm)	405	435	465
Seat Tube Angle	74.5°	74.5°	74.0°
Top Tube Length (mm)	520	525	535
Head Tube Length (mm)	125	145	165
Head Tube Angle	71.0°	71.0°	71.0°
Fork Rake (mm)	50	50	50
Trail (mm)	67.8	67.8	67.8
Wheelbase (mm)	995.7	1002	1007.9
Chain Stay Length (mm)	420	420	420
Bottom Bracket Drop (mm)	75	75	75
Stack (mm)	528.6	547.6	566.5
Reach (mm)	373.4	373.1	372.6
Stand Over Height (mm)	686.4	712	737
Stem Length (mm)	70	80	90
Crank Length (mm)	165	170	170
Wheel Size	700C	700C	700C

Please note that our specifications may be impacted by running substitution changes, we highly recommend confirming the specifications of our products with your local retailer at the time of sale if purchasing in-store. *Recommended Retail Prices are subject to change without notice and may vary from store to store depending on freight and assembly costs.