BELIV SL 1



SPECS

FRAME	
SIZES	XXS, XS, S, M, L
FRAME	ALUXX SL-grade aluminum, 12x142mm thru-axle, disc
FORK	Advanced-grade composite, full-composite OverDrive steerer, 12x100mm, disc
COMPONENTS	
HANDLEBAR	Giant Contact, 31.8mm, 7.2 degree flare XXS: 350mm, XS: 350mm, S: 370mm, M: 370mm, L: 390mm
GRIPS	Cork (Gel) Tape VLT-001G
STEM	Giant Contact AeroLight, XXS: 80mm, XS: 80mm, S: 90mm, M: 90mm, L: 350mm
SEATPOST	Giant D-Fuse, alloy, XXS: 300mm, XS: 300mm, S: 350mm, M: 350mm, L: 350mm
SADDLE	Liv Grit
DRIVETRAIN	
SHIFTERS	Shimano Tiagra
FRONT DERAILLEUR	Shimano Tiagra
REAR DERAILLEUR	Shimano Tiagra R4000
BRAKES	Shimano Tiagra, Giant MPH rotors, [F]160mm, [R]140mm
BRAKE LEVERS	Shimano Tiagra R4000
CASSETTE	Shimano CS-RS400-11, 11X36, 11 speed
CHAIN	KMC X11
CRANKSET	Shimano FC-R4000, 50/34
BOTTOM BRACKET	Shimano, PressFit RS500

WHEELS	
RIMS	Giant ALP Disc
HUBS	Giant alloy, 12mm thru-axle
SPOKES	stainless
TIRES	Giant SR 1 700X28C, 60 TPI
LIMITS	
MAX TIRE CLEARANCE	700x33mm

Recommended Retail Price: $1,300.00

GEOMETRY

FRAME	XXS	XS	S	M	L
Seat Tube Length (inch)	15.2	15.9	17.1	18.3	19.5
Seat Tube Angle	75.0°	74.5°	74.5°	74.0°	74.0°
Top Tube Length (inch)	19.7	20.5	20.7	21.1	21.7
Head Tube Length (inch)	4.3	4.9	5.7	6.5	7.3
Head Tube Angle	69.8°	71.0°	71.0°	71.0°	72.0°
Fork Rake (inch)	2	2	2	2	2
Trail (inch)	3	2.6	2.6	2.6	2.4
Wheelbase (inch)	38.9	39.2	39.4	39.6	39.9
Chain Stay Length (inch)	16.5	16.5	16.5	16.5	16.5
Bottom Bracket Drop (inch)	3	3	3	3	3
Stack (inch)	20.1	20.8	21.5	22.3	23.2
Reach (inch)	14.3	14.7	14.7	14.6	15
Stand Over Height (inch)	26.3	27	28	29	30.4
Handlebar Width (inch)	13.8	13.8	14.6	14.6	15.4
Stem Length (inch)	2.8	2.8	3.1	3.5	3.5
Crank Length (inch)	6.5	6.5	6.7	6.7	6.8
Wheel Size	700C	700C	700C	700C	700C

**All specifications and prices listed are subject to change without notice.*
Actual weight may vary due to manufacturing tolerances, color variations, frame size and variability in production components.