BELIV SL 1



SPECS

FRAME	
SIZES	XXS, XS, S, M, L
FRAME	ALUXX SL-grade aluminum, 12x142mm thru-axle, disc
FORK	Advanced-grade composite, full-composite OverDrive steerer, 12x100mm, disc
COMPONENTS	
HANDLEBAR	Giant Contact, 31.8mm, 7.2 degree flare XXS: 350mm, XS: 350mm, S: 370mm, M: 370mm, L: 390mm
GRIPS	Cork (Gel) Tape VLT-001G
STEM	Giant Contact AeroLight, XXS: 80mm, XS: 80mm, S: 90mm, M: 90mm, L: 350mm
SEATPOST	Giant D-Fuse, alloy, XXS: 300mm, XS: 300mm, S: 350mm, M: 350mm, L: 350mm
SADDLE	Liv Grit
DRIVETRAIN	
SHIFTERS	Shimano Tiagra
FRONT DERAILLEUR	Shimano Tiagra
REAR DERAILLEUR	Shimano Tiagra R4000
BRAKES	Shimano Tiagra, Giant MPH rotors, [F]160mm, [R]140mm
BRAKE LEVERS	Shimano Tiagra R4000
CASSETTE	Shimano CS-RS400-11, 11X36, 11 speed
CHAIN	KMC X11
CRANKSET	Shimano FC-R4000, 50/34
BOTTOM BRACKET	Shimano, PressFit RS500

WHEELS	
RIMS	Giant ALP Disc
HUBS	Giant alloy, 12mm thru-axle
SPOKES	stainless
TIRES	Giant SR 1 700X28C, 60 TPI
LIMITS	
MAX TIRE CLEARANCE	700x33mm

Suggested Retail Price (CDN): $2,299.00

FRAME GEOMETRY

FRAME	XXS	XS	S
Seat Tube Length (mm)	385	405	435
Seat Tube Angle	75.0°	74.5°	74.5°
Top Tube Length (mm)	500	520	525
Head Tube Length (mm)	110	125	145
Head Tube Angle	69.8°	71.0°	71.0°
Fork Rake (mm)	50	50	50
Trail (mm)	75.7	67.8	67.8
Wheelbase (mm)	989.9	995.7	1002
Chain Stay Length (mm)	420	420	420
Bottom Bracket Drop (mm)	75	75	75
Stack (mm)	510.1	528.6	547.6
Reach (mm)	363.3	373.4	373.1
Stand Over Height (mm)	669.1	686.4	712
Handlebar Width (mm)	350	350	370
Stem Length (mm)	70	70	80
Crank Length (mm)	165	165	170
Wheel Size	700C	700C	700C

All prices and specifications are subject to change without notice.