BELIV SL 1



SPECS

TELAIO	
TAGLIE	XXS, XS, S, M, L
TELAIO	ALUXX SL-grade aluminum, 12x142mm thru-axle, disc
FORCELLA	Advanced-grade composite, full-composite OverDrive steerer, 12x100mm, disc
COMPONENTISTICA	
MANUBRIO	Giant Contact, 31.8mm, 7.2 degree flare XXS: 350mm, XS: 350mm, S: 370mm, M: 370mm, L: 390mm
MANOPOLE	Cork (Gel) Tape VLT-001G
ATTACCO MANUBRIO	Giant Contact AeroLight, XXS: 80mm, XS: 80mm, S: 90mm, M: 90mm, L: 350mm
REGGISELLA	Giant D-Fuse, alloy, XXS: 300mm, XS: 300mm, S: 350mm, M: 350mm, L: 350mm
SELLA	Liv Grit
SISTEMA DI TRASMISSIONE	
CAMBIO	Shimano Tiagra
DERAGLIATORE ANTERIORE	Shimano Tiagra
DERAGLIATORE POSTERIORE	Shimano Tiagra R4000
FRENI	Shimano Tiagra, Giant MPH rotors, [F]160mm, [R]140mm
COMANDI FRENO	Shimano Tiagra R4000
PACCO PIGNONI	Shimano CS-RS400-11, 11X36, 11 speed
CATENA	KMC X11
GUARNITURA	Shimano FC-R4000, 50/34
MOVIMENTO CENTRALE	Shimano, PressFit RS500

RUOTE	
CERCHI	Giant ALP Disc
MOZZI	Giant alloy, 12mm thru-axle
RAGGI	stainless
COPERTONI	Giant SR 1 700X28C, 60 TPI
LIMITI	
SEZIONE MASSIMA SUPPORTATA	700x33mm

Prezzo: 1.599,00 €

GEOMETRIA

TELAIO	XXS	XS	S	M	L
Lunghezza Tubo Sella (mm)	385	405	435	465	495
Angolo Tubo Sella	75,0°	74,5°	74,5°	74,0°	74,0°
Lunghezza Tubo Orizzontale (mm)	500	520	525	535	550
Lunghezza Tubo Sterzo (mm)	110	125	145	165	185
Angolo Sterzo	69,8°	71,0°	71,0°	71,0°	72,0°
Rake Forcella (mm)	50	50	50	50	50
Avancorsa (mm)	75,7	67,8	67,8	67,8	61,3
Interasse (mm)	989,9	995,7	1002	1007,9	1013,9
Lunghezza Carro Posteriore (mm)	420	420	420	420	420
Drop Movimento Centrale (mm)	75	75	75	75	75
Stack (mm)	510,1	528,6	547,6	566,5	589,3
Reach (mm)	363,3	373,4	373,1	372,6	381
Altezza stand over (mm)	669,1	686,4	712	737	771,4
Larghezza Manubrio c/c (mm)	350	350	370	370	390
Lunghezza Attacco Manubrio (mm)	70	70	80	90	90
Lunghezza Pedivella (mm)	165	165	170	170	172,5
Dimensione Ruote	700C	700C	700C	700C	700C

Le specifiche tecniche e i colori sono soggette a variazioni senza obbligo di preavviso. Verifica la disponibilità con il tuo rivenditore Giant e Liv di fiducia.