

# BRAVA ADVANCED PRO 0



## SPECS

FRAME	
SIZES	XS, S, M
COLOURS	Orion Nebula/Carbon/Chrome
FRAME	Advanced-Grade Composite, 12mm thru-axle, disc
FORK	Advanced-Grade Composite, full-composite OverDrive 2 steerer, disc
SHOCK	N/A
COMPONENTS	
HANDLEBAR	Giant Contact SLR
GRIPS	Liv All Condition
STEM	Giant Contact SL
SEATPOST	Giant D-Fuse SLR, composite, -5/+15mm offset
SADDLE	Liv Approach SL
PEDALS	N/A
DRIVETRAIN	
SHIFTERS	SRAM Force eTap AXS, 1x12
FRONT DERAILLEUR	N/A
REAR DERAILLEUR	SRAM Force eTap AXS
BRAKES	SRAM Force eTap AXS hydraulic, SRAM CenterLine rotors [F]160mm, [R]140mm
BRAKE LEVERS	SRAM Force eTap AXS hydraulic
CASSETTE	SRAM Force, 12-speed, 10x36
CHAIN	SRAM Force D1
CRANKSET	SRAM Force D1 DUB, 38t
BOTTOM BRACKET	SRAM DUB, press fit

WHEELS	
RIMS	Giant CXR 1 Carbon Disc WheelSystem
HUBS	[F] Giant AR alloy, CenterLock, 12mm thru-axle, [R] Giant AR alloy, DT350 36t ratchet system, CenterLock, 12mm thru-axle
SPOKES	Sapim CX-Ray
TYRES	Maxxis All-Terrane, 700x33c, tubeless
EXTRAS	Giant 1x chainguide, 45mm max tyre size

**Price: \$7,799.00**

## GEOMETRY

FRAME	XS	S	M
Seat Tube Length (mm)	490	505	520
Seat Tube Angle	74.0°	74.0°	73.5°
Top Tube Length (mm)	510	520	535
Head Tube Length (mm)	108	123	138
Head Tube Angle	70.3°	71.0°	71.5°
Fork Rake (mm)	50	50	50
Trail (mm)	72.9	68.3	65.1
Wheelbase (mm)	1004	1009	1014
Chain Stay Length (mm)	430	430	430
Bottom Bracket Drop (mm)	60	60	60
Stack (mm)	514	531	547
Reach (mm)	363	368	373
Stand Over Height (mm)	773	788	802
Stem Length (mm)	70	80	90
Crank Length (mm)	165	170	170
Wheel Size	700C	700C	700C

Please note that our specifications may be impacted by running substitution changes, we highly recommend confirming the specifications of our products with your local retailer at the time of sale if purchasing in-store. \*Recommended Retail Prices are subject to change without notice and may vary from store to store depending on freight and assembly costs.