

# BRAVA ADVANCED PRO 1



## SPECIFICATIES

FRAME	
MATEN	XS, S, M, L
KLEUREN	Dark Iridescent/Carbon/Chrome
FRAME	Advanced-Grade Composite, 12mm thru-axle, disc
VOORVORK	Advanced-Grade Composite, full-composite OverDrive 2 steerer, disc
DEMPER	N/A
ONDERDELEN	
STUUR	Giant Contact SL XS:38cm, S:38cm, M:40cm, L:40cm
HANDVATTEN	Liv All Condition
STUURPEN	Giant Contact SL XS:70mm, S:80mm, M:90mm, L:90mm
ZADELPEN	Giant D-Fuse SLR, composite, -5/+15mm offset
ZADEL	Liv Alacra SL CS
PEDALEN	platform pedal
AFMONTAGE	
SHIFTERS	Shimano GRX RX-810, 1x11
VOORDERAILLEUR	N/A
ACHTERDERAILLEUR	Shimano GRX RX-810
REMMEN	Shimano GRX RX-810 hydraulic, Shimano SM-RT800 rotors [F]160mm, [R]140mm
REMHENDELS	Shimano GRX RX-810 hydraulic
CASSETTE	Shimano Ultegra, 11-speed, 11x34
AANDRIJVING	KMC X11SL-1
CRANKSET	Shimano GRX RX-810, 40t XS:170mm, S:170mm, M:170mm, L:172.5mm
BOTTOM BRACKET	Shimano, press fit

WIELSET	
VELGEN	Giant SLR-2 42 Carbon Disc WheelSystem
NAVEN	Giant SLR-2 42 Carbon Disc WheelSystem
SPAKEN	Giant SLR-2 42 Carbon Disc WheelSystem
BANDEN	Maxxis All-Terrane, 700x33c, tubeless
EXTRA'S	tubeless prepared, 45mm max tire size

Adviesprijs: € 4.299,00

## GEOMETRIE

FRAME	XS	S	M	L
Zitbuis Lengte (mm)	490	505	520	535
Zitbuis Hoek	74,0°	74,0°	73,5°	73,0°
Frame Lengte (horizontaal) (mm)	510	520	535	550
Balhoofdbuis Lengte (mm)	108	123	138	158
Balhoofdbuis Hoek	70,3°	71,0°	71,5°	71,5°
Vork Sprong (mm)	50	50	50	50
Naloop (mm)	72,9	68,3	65,1	65,1
Wielbasis (mm)	1004	1009	1014	1025
Liggende achtervork lengte (mm)	430	430	430	430
Bottom Bracket Drop (mm)	60	60	60	60
Stack (mm)	514	531	547	566
Reach (mm)	363	368	373	377
Stand Over Height (mm)	773	788	802	817
Stuur breedte (mm)	380	380	400	400
Stuurpen Lengte (mm)	70	80	90	90
Cranklengte (mm)	165	170	170	172,5
Wielmaat	700C	700C	700C	700C

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder voorafkondiging wijzigen.