

# BRAVA ADVANCED PRO 2



## SPECIFIKACIJE

OKVIR	
VELIČINE	XS, S, M, L
BOJE	Digital Blurple
OKVIR	Advanced-grade composite, 12mm thru-axle, disc
VILICA	Advanced-grade composite, full-composite OverDrive 2 steerer, disc
AMORTIZER	N/A
KOMPONENTE	
VOLAN	Giant Connect XS: 380mm, S: 380mm, M: 400mm, L: 400mm
GRIPS	Liv All Condition
LULA VOLANA	Giant Contact XS: 70mm, S: 80mm, M: 90mm, L: 90mm
CIJEV SJEDALA	Giant D-Fuse SL, composite, -5/+15mm offset
SJEDALO	Liv Approach
PEDALE	no pedal [GA, Pan-Eu] platform pedal [GU, GV, GJ] pedal w/toeclip and strap [All other GSC]
POGON	
RUČICE MJENJAČA	SRAM Apex, 1x12
PREDNJI MJENJAČ	N/A
STRAŽNJI MJENJAČ	SRAM Apex
KOČNICE	SRAM Apex hydraulic, Giant MPH rotors [F]160mm, [R]140mm
RUČICE KOČNICA	SRAM Apex hydraulic
KAZETA	SRAM Apex XPLR, 12-speed, 11x44
LANAC	SRAM Apex D1
POGON	SRAM Apex, 40t XS: 165mm, S: 170mm, M: 170mm, L: 172.5mm
OSOVINA POGONA (BB)	SRAM DUB, press fit

KOTAČI	
OBRUČI	Giant P-X2 Disc wheelset, alloy
NABE	Giant alloy, 12mm thru-axle
ŽBICE	Sapim
GUME	Maxxis All-Terrane, 700x33c, tubeless
DODACI	2 sets of water bottle cage bolts, 45mm max tire size

## GEOMETRIJA

OKVIR	XS	S	M	L
Dužina cijevi sjedala (mm)	490	505	520	535
Kut cijevi sjedala	74,0°	74,0°	73,5°	73,0°
Dužina gornje cijevi (mm)	510	520	535	550
Dužina prednje cijevi (mm)	108	123	138	158
Kut vilice	70,3°	71,0°	71,5°	71,5°
Zakrivljenost vilice (offset) (mm)	50	50	50	50
Staza (mm)	72,9	68,3	65,1	65,1
Međuosovinski razmak kotača (mm)	1004	1009	1014	1025
Dužina od osovine pogona do osovine zadnjeg kotača (CS) (mm)	430	430	430	430
Položaj osovine pogona (mm)	60	60	60	60
Vertikalna dužina od osovine pogona do glave okvira (stack) (mm)	514	531	547	566
Horizontalna dužina od osovine pogona do glave okvira (reach) (mm)	363	368	373	377
Prekoračna visina (mm)	773	788	802	817
Širina volana (mm)	380	380	400	400
Dužina lule volana (mm)	70	80	90	90
Dužina poluge pedale (mm)	165	170	170	172,5
Veličina kotača	700C	700C	700C	700C

Sve navedene specifikacije podložne su promjeni bez prethodne najave.