



SPECS

FRAME	
SIZES	XS, S, M, L
COLORS	Digital Blurple
FRAME	Advanced-grade composite, 12mm thru-axe, disc
FORK	Advanced-grade composite, full-composite OverDrive 2 steerer, disc
SHOCK	N/A
COMPONENTS	
HANDLEBAR	Giant Connect XS: 380mm, S: 380mm, M: 400mm, L: 400mm
GRIPS	Liv All Condition
STEM	Giant Contact XS: 70mm, S: 80mm, M: 90mm, L: 90mm
SEATPOST	Giant D-Fuse SL, composite, -5/+15mm offset
SADDLE	Liv Approach
PEDALS	no pedal [GA, Pan-Eu] platform pedal [GU, GV, GJ] pedal w/toeclip and strap [All other GSC]
DRIVETRAIN	
SHIFTERS	SRAM Apex, 1x12
FRONT DERAILLEUR	N/A
REAR DERAILLEUR	SRAM Apex
BRAKES	SRAM Apex hydraulic, Giant MPH rotors [F]160mm, [R]140mm
BRAKE LEVERS	SRAM Apex hydraulic
CASSETTE	SRAM Apex XPLR, 12-speed, 11x44
CHAIN	SRAM Apex D1
CRANKSET	SRAM Apex, 40t XS: 165mm, S: 170mm, M: 170mm, L: 172.5mm
BOTTOM BRACKET	SRAM DUB, press fit

WHEELS	
RIMS	Giant P-X2 Disc wheelset, alloy
HUBS	Giant alloy, 12mm thru-axe
SPOKES	Sapim
TIRES	Maxxis All-Terrane, 700x33c, tubeless
EXTRAS	2 sets of water bottle cage bolts, 45mm max tire size

GEOMETRY

FRAME	XS	S	M	L
Seat Tube Length (mm)	490	505	520	535
Seat Tube Angle	74,0°	74,0°	73,5°	73,0°
Top Tube Length (mm)	510	520	535	550
Head Tube Length (mm)	108	123	138	158
Head Tube Angle	70,3°	71,0°	71,5°	71,5°
Fork Rake (mm)	50	50	50	50
Trail (mm)	72,9	68,3	65,1	65,1
Wheelbase (mm)	1004	1009	1014	1025
Chain Stay Length (mm)	430	430	430	430
Bottom Bracket Drop (mm)	60	60	60	60
Stack (mm)	514	531	547	566
Reach (mm)	363	368	373	377
Stand Over Height (mm)	773	788	802	817
Handlebar Width (mm)	380	380	400	400
Stem Length (mm)	70	80	90	90
Crank Length (mm)	165	170	170	172,5
Wheel Size	700C	700C	700C	700C

All specifications listed are subject to change without notice.