

BRAVA ADVANCED PRO 2



SPECS

RAMME	
STØRRELSE	XS, S, M, L
FARGE	Digital Blurple
RAMME	Advanced-grade composite, 12mm thru-axle, disc
GAFFEL	Advanced-grade composite, full-composite OverDrive 2 steerer, disc
DEMPER	N/A
KOMPONENTER	
STYRE	Giant Connect XS: 380mm, S: 380mm, M: 400mm, L: 400mm
GRIPS	Liv All Condition
STYRSTEM	Giant Contact XS: 70mm, S: 80mm, M: 90mm, L: 90mm
SETEPINNE	Giant D-Fuse SL, composite, -5/+15mm offset
SADEL	Liv Approach
PEDALER	no pedal [GA, Pan-Eu] platform pedal [GU, GV, GJ] pedal w/toeclip and strap [All other GSC]
DRIVVERK	
GIRHENDLER	SRAM Apex, 1x12
FRONTGIR	N/A
BAKGIR	SRAM Apex
BREMSE	SRAM Apex hydraulic, Giant MPH rotors [F]160mm, [R]140mm
BREMSEHENDLER	SRAM Apex hydraulic
KASSETT	SRAM Apex XPLR, 12-speed, 11x44
KJEDE	SRAM Apex D1
KRANK	SRAM Apex, 40t XS: 165mm, S: 170mm, M: 170mm, L: 172.5mm
BOTTOM BRACKET	SRAM DUB, press fit

HJUL	
FELG	Giant P-X2 Disc wheelset, alloy
NAV	Giant alloy, 12mm thru-axle
EIKE	Sapim
DEKK	Maxxis All-Terrane, 700x33c, tubeless
EXTRAS	2 sets of water bottle cage bolts, 45mm max tire size

GEOMETRI

RAMME	XS	S	M	L
Seat Tube Length (mm)	490	505	520	535
Seat Tube Angle	74,0°	74,0°	73,5°	73,0°
Top Tube Length (mm)	510	520	535	550
Head Tube Length (mm)	108	123	138	158
Head Tube Angle	70,3°	71,0°	71,5°	71,5°
Fork Rake (mm)	50	50	50	50
Trail (mm)	72,9	68,3	65,1	65,1
Wheelbase (mm)	1004	1009	1014	1025
Chain Stay Length (mm)	430	430	430	430
Bottom Bracket Drop (mm)	60	60	60	60
Stack (mm)	514	531	547	566
Reach (mm)	363	368	373	377
Stand Over Height (mm)	773	788	802	817
Handlebar Width (mm)	380	380	400	400
Stem Length (mm)	70	80	90	90
Crank Length (mm)	165	170	170	172,5
Wheel Size	700C	700C	700C	700C

Alle spesifikasjonene kan endres uten varsel.