



## ŠPECIFIKÁCIE

RÁM	
VELKOSTI	XS, S, M, L
FARBY	Digital Blurple
RÁM	Advanced-grade composite, 12mm thru-axle, disc
VIDLICA	Advanced-grade composite, full-composite OverDrive 2 steerer, disc
TLMIČ	N/A
KOMPONENTY	
RIADIDLÁ	Giant Connect XS: 380mm, S: 380mm, M: 400mm, L: 400mm
GRIPY	Liv All Condition
PREDSTAVEC	Giant Contact XS: 70mm, S: 80mm, M: 90mm, L: 90mm
SEDOVKA	Giant D-Fuse SL, composite, -5/+15mm offset
SEADLO	Liv Approach
PEDÁLE	no pedal [GA, Pan-Eu] platform pedal [GU, GV, GJ] pedal w/toeclip and strap [All other GSC]
POHON	
RADENIE	SRAM Apex, 1x12
PREŠMYKAČ	N/A
PREHADZOVAČKA	SRAM Apex
BRZDY	SRAM Apex hydraulic, Giant MPH rotors [F]160mm, [R]140mm
BRZDOVÉ PÁKY	SRAM Apex hydraulic
KAZETA	SRAM Apex XPLR, 12-speed, 11x44
REŤAZ	SRAM Apex D1
KLUKY	SRAM Apex, 40t XS: 165mm, S: 170mm, M: 170mm, L: 172.5mm
STREDOVÉ ZLOŽENIE	SRAM DUB, press fit

KOLESÁ	
RÁFIKY	Giant P-X2 Disc wheelset, alloy
NÁBOJE	Giant alloy, 12mm thru-axle
ŠPICE	Sapim
PNEUMATIKY	Maxxis All-Terrane, 700x33c, tubeless
DOPLNKY	2 sets of water bottle cage bolts, 45mm max tire size

Cena: 3 199 €

## GEOMETRIA

RÁM	XS	S	M	L
Dĺžka sedlovej trubky (mm)	490	505	520	535
Uhol sedlovej trubky	74,0°	74,0°	73,5°	73,0°
Dĺžka hornej rámovej trubky (mm)	510	520	535	550
Dĺžka hlavovej trubky (mm)	108	123	138	158
Uhol hlavovej trubky	70,3°	71,0°	71,5°	71,5°
Offset vidlice (mm)	50	50	50	50
Trail (mm)	72,9	68,3	65,1	65,1
Rázvor (mm)	1004	1009	1014	1025
Dĺžka zadnej stavby (mm)	430	430	430	430
Rozdiel zadnej voči stredovej osi - BB DROP (mm)	60	60	60	60
Stack - výška riadenia (mm)	514	531	547	566
Reach (mm)	363	368	373	377
Výška rámu od zeme (mm)	773	788	802	817
Šírka riaditok (mm)	380	380	400	400
Dĺžka predstavca (mm)	70	80	90	90
Dĺžka klúku (mm)	165	170	170	172,5
Rozmer kolies	700C	700C	700C	700C

Všetky ceny a špecifikácie sa môžu zmeniť bez predchádzajúceho upozornenia.