

BRAVA ADVANCED PRO 2



SPECIFIKACIJE

OKVIR	
VELIKOSTI	XS, S, M, L
BARVE	Digital Blurple
OKVIR	Advanced-grade composite, 12mm thru-axle, disc
VILICE	Advanced-grade composite, full-composite OverDrive 2 steerer, disc
AMORTIZER	N/A
KOMPONENTE	
KRMILO	Giant Connect XS: 380mm, S: 380mm, M: 400mm, L: 400mm
GRIPS	Liv All Condition
OPORA KRMILA	Giant Contact XS: 70mm, S: 80mm, M: 90mm, L: 90mm
OPORA SEDEŽA	Giant D-Fuse SL, composite, -5/+15mm offset
SEDEŽ	Liv Approach
PEDALA	no pedal [GA, Pan-Eu] platform pedal [GU, GV, GJ] pedal w/toeclip and strap [All other GSC]
POGON	
PRESTAVNE ROČICE	SRAM Apex, 1x12
PREDNJI MENJALNIK	N/A
ZADNJI MENJALNIK	SRAM Apex
ZAVORE	SRAM Apex hydraulic, Giant MPH rotors [F]160mm, [R]140mm
ZAVORNE ROČICE	SRAM Apex hydraulic
VERIŽNIK	SRAM Apex XPLR, 12-speed, 11x44
VERIGA	SRAM Apex D1
GONILKE Z VERIŽNIKI	SRAM Apex, 40t XS: 165mm, S: 170mm, M: 170mm, L: 172.5mm
BOTTOM BRACKET	SRAM DUB, press fit

OBROČNIKI	
OBROČI	Giant P-X2 Disc wheelset, alloy
PESTA	Giant alloy, 12mm thru-axle
NAPERE	Sapim
PLAŠČI	Maxxis All-Terrane, 700x33c, tubeless
DODATKI	2 sets of water bottle cage bolts, 45mm max tire size

GEOMETRIJA

OKVIR	XS	S	M	L
Dolžina sedežne cevi (mm)	490	505	520	535
Kot sedežne cevi	74,0°	74,0°	73,5°	73,0°
Top Tube Length (mm)	510	520	535	550
Višina glave okvirja (mm)	108	123	138	158
Krmlni kot	70,3°	71,0°	71,5°	71,5°
Zamik vpetja osi (mm)	50	50	50	50
Trail (mm)	72,9	68,3	65,1	65,1
Medosna razdalja (mm)	1004	1009	1014	1025
Dolžina cevi ob verigi (mm)	430	430	430	430
Bottom Bracket Drop (mm)	60	60	60	60
Oddaljenost zgornje cevi od gonilne osi (mm)	514	531	547	566
Doseg (mm)	363	368	373	377
Višina zgornje cevi (mm)	773	788	802	817
Širina krmila (mm)	380	380	400	400
Dolžina opore krmila (mm)	70	80	90	90
Dolžina gonilke (mm)	165	170	170	172,5
Velikost obročnikov	700C	700C	700C	700C

Vse navedene specifikacije se lahko spremenijo brez obvestila.