DEVOTE 0

SPECS

FRAME	
SIZES	XS, S, M, L
COLORS	Clear Sky
FRAME	ALUXX-grade aluminum, 12x142mm thru-axle, flat mount disc, flip chip – dropout
FORK	Advanced-grade composite, full-composite OverDrive steerer, 12mm thru-axle, flat mount disc
SHOCK	N/A
COMPONENTS	
HANDLEBAR	Giant Contact XR D-Fuse, 31.8mm, 5-degree back sweep, flare drop, XS: 400mm, S: 400mm, M: 420mm, L: 420mm
GRIPS	Cork Tape w/ Gel VLT004-02
STEM	Giant Contact, 8-degree, XS: 50mm, S: 60mm, M: 70mm, L: 80mm
SEATPOST	Giant D-Fuse, alloy
SADDLE	Liv Grit
DRIVETRAIN	
SHIFTERS	Shimano GRX RX-610, 2x12
FRONT DERAILLEUR	Shimano GRX RX-820
REAR DERAILLEUR	Shimano GRX RX-820
BRAKES	Shimano GRX BR-RX410 hydraulic, Giant MPH rotors, [F]160mm, [R]160mm
BRAKE LEVERS	Shimano GRX RX-610 hydraulic
CASSETTE	Shimano 105, 12-speed, 11x34
CHAIN	KMC X12L-1
CRANKSET	Shimano FC-RX610, 30/46, XS: 165mm, S: 170mm, M: 172.5mm, L: 172.5mm
BOTTOM BRACKET	Shimano, press fit

WHEELS	
RIMS	Giant S-X2 Disc, alloy
HUBS	Giant alloy, 12mm thru-axle
SPOKES	stainless steel
TIRES	CrossCut GRIP 1; 700x45c
EXTRAS	53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position, tubeless prepared, ISC clamp
LIMITS	
MAX TIRE CLEARANCE	53mm

GEOMETRY

FRAME	XS	S	M	L
	SHORT | LONG	SHORT | LONG	SHORT | LONG	SHORT | LONG
Seat Tube Length (mm)	390	420	465	500
Seat Tube Angle	74,5° | 74,4°	74,5° | 74,4°	74,5° | 74,4°	74,5° | 74,4°
Top Tube Length (mm)	525 | 525	535 | 535	545 | 545	555 | 555
Head Tube Length (mm)	90	110	140	160
Head Tube Angle	70,0° | 69,9°	70,5° | 70,4°	71,0° | 70,9°	71,0° | 70,9°
Fork Rake (mm)	50	50	50	50
Trail (mm)	78,4 | 82	75 | 78,5	71,6 | 75,1	71,6 | 75
Wheelbase (mm)	1017 | 1027	1024 | 1034	1031 | 1041	1043 | 1052
Chain Stay Length (mm)	430 | 440	430 | 440	430 | 440	430 | 440
Bottom Bracket Drop (mm)	80 | 81	80 | 81	80 | 81	80 | 81
Stack (mm)	523 | 524	544 | 545	574 | 575	593 | 594
Reach (mm)	380 | 379	384 | 383	386 | 385	391 | 389
Stand Over Height (mm)	681 | 688	708 | 715	748 | 755	779 | 786
Handlebar Width (mm)	400	400	420	420
Stem Length (mm)	50	60	70	80
Crank Length (mm)	165	170	172,5	172,5

All specifications listed are subject to change without notice.