

DEVOTE 0



SPEZIFIKATIONEN

RAHMEN	
GRÖSSEN	XS, S, M, L
FARBE	Clear Sky
RAHMEN	ALUXX-grade aluminum, 12x142mm thru-axle, flat mount disc, flip chip – dropout
GABEL	Advanced-grade composite, full-composite OverDrive steerer, 12mm thru-axle, flat mount disc
DÄMPFER	N/A
KOMPONENTEN	
LENKER	Giant Contact XR D-Fuse, 31.8mm, 5-degree back sweep, flare drop, XS: 400mm, S: 400mm, M: 420mm, L: 420mm
GRIFFE	Cork Tape w/ Gel VLT004-02
VORBAU	Giant Contact, 8-degree, XS: 50mm, S: 60mm, M: 70mm, L: 80mm
SATTELSTÜTZE	Giant D-Fuse, alloy
SATTEL	Liv Grit
ANTRIEB	
SCHALTHEBEL	Shimano GRX RX-610, 2x12
UMWERFER	Shimano GRX RX-820
SCHALTWERK	Shimano GRX RX-820
BREMSEN	Shimano GRX BR-RX410 hydraulic, Giant MPH rotors, [F]160mm, [R]160mm
BREMSEBEL	Shimano GRX RX-610 hydraulic
KASSETTE	Shimano 105, 12-speed, 11x34
KETTE	KMC X12L-1
KURBEL	Shimano FC-RX610, 30/46, XS: 165mm, S: 170mm, M: 172.5mm, L: 172.5mm
TRETLAGER	Shimano, press fit

LAUFRÄDER	
FELGEN	Giant S-X2 Disc, alloy
NABE	Giant alloy, 12mm thru-axle
SPEICHEN	stainless steel
REIFEN	CrossCut GRIP 1; 700x45c
EXTRAS	53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position, tubeless prepared, ISC clamp
LIMITS	
MAX TIRE CLEARANCE	53mm

GEOMETRIEDATEN

RAHMEN	XS		S		M		L	
	SHORT	LONG	SHORT	LONG	SHORT	LONG	SHORT	LONG
Sitzrohrlänge (mm)	390		420		465		500	
Sitzrohrwinkel	74.5°	74.4°	74.5°	74.4°	74.5°	74.4°	74.5°	74.4°
Oberrohrlänge (mm)	525	525	535	535	545	545	555	555
Steuerrohr-Länge (mm)	90		110		140		160	
Steuerrohr-Winkel	70.0°	69.9°	70.5°	70.4°	71.0°	70.9°	71.0°	70.9°
Gabelneigung (mm)	50		50		50		50	
Trail (mm)	78.4	82	75	78.5	71.6	75.1	71.6	75
Radstand (mm)	1017	1027	1024	1034	1031	1041	1043	1052
Kettenstreben-Länge (mm)	430	440	430	440	430	440	430	440
Tretlager-Höhe (mm)	80	81	80	81	80	81	80	81
Stack (mm)	523	524	544	545	574	575	593	594
Reach (mm)	380	379	384	383	386	385	391	389
Überstandshöhe (mm)	681	688	708	715	748	755	779	786
Lenkerbreite (mm)	400		400		420		420	
Vorbaulänge (mm)	50		60		70		80	
Kurbellänge (mm)	165		170		172.5		172.5	

Spezifikations-, Preis- und Farbänderungen vorbehalten.