

DEVOTE 0



SPECS

FRAME	
SIZES	XS, S, M, L
COLORS	Clear Sky
FRAME	ALUXX-grade aluminum, 12x142mm thru-axle, flat mount disc, flip chip – dropout
FORK	Advanced-grade composite, full-composite OverDrive steerer, 12mm thru-axle, flat mount disc
SHOCK	N/A
COMPONENTS	
HANDLEBAR	Giant Contact XR D-Fuse, 31.8mm, 5-degree back sweep, flare drop, XS: 400mm, S: 400mm, M: 420mm, L: 420mm
GRIPS	Cork Tape w/ Gel VLT004-02
STEM	Giant Contact, 8-degree, XS: 50mm, S: 60mm, M: 70mm, L: 80mm
SEATPOST	Giant D-Fuse, alloy
SADDLE	Liv Grit
DRIVETRAIN	
SHIFTERS	Shimano GRX RX-610, 2x12
FRONT DERAILLEUR	Shimano GRX RX-820
REAR DERAILLEUR	Shimano GRX RX-820
BRAKES	Shimano GRX BR-RX410 hydraulic, Giant MPH rotors, [F]160mm, [R]160mm
BRAKE LEVERS	Shimano GRX RX-610 hydraulic
CASSETTE	Shimano 105, 12-speed, 11x34
CHAIN	KMC X12L-1
CRANKSET	Shimano FC-RX610, 30/46, XS: 165mm, S: 170mm, M: 172.5mm, L: 172.5mm
BOTTOM BRACKET	Shimano, press fit

WHEELS	
RIMS	Giant S-X2 Disc, alloy
HUBS	Giant alloy, 12mm thru-axle
SPOKES	stainless steel
TIRES	CrossCut GRIP 1; 700x45c
EXTRAS	53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position, tubeless prepared, ISC clamp
LIMITS	
MAX TIRE CLEARANCE	53mm

GEOMETRY

FRAME	XS		S		M		L	
	SHORT	LONG	SHORT	LONG	SHORT	LONG	SHORT	LONG
Seat Tube Length (mm)	390		420		465		500	
Seat Tube Angle	74,5°	74,4°	74,5°	74,4°	74,5°	74,4°	74,5°	74,4°
Top Tube Length (mm)	525	525	535	535	545	545	555	555
Head Tube Length (mm)	90		110		140		160	
Head Tube Angle	70,0°	69,9°	70,5°	70,4°	71,0°	70,9°	71,0°	70,9°
Fork Rake (mm)	50		50		50		50	
Trail (mm)	78,4	82	75	78,5	71,6	75,1	71,6	75
Wheelbase (mm)	1017	1027	1024	1034	1031	1041	1043	1052
Chain Stay Length (mm)	430	440	430	440	430	440	430	440
Bottom Bracket Drop (mm)	80	81	80	81	80	81	80	81
Stack (mm)	523	524	544	545	574	575	593	594
Reach (mm)	380	379	384	383	386	385	391	389
Stand Over Height (mm)	681	688	708	715	748	755	779	786
Handlebar Width (mm)	400		400		420		420	
Stem Length (mm)	50		60		70		80	
Crank Length (mm)	165		170		172,5		172,5	

All specifications listed are subject to change without notice.