

DEVOTE 0



SPEZIFIKATIONEN

RAHMEN	
GRÖSSEN	XS, S, M, L
FARBE	Clear Sky
RAHMEN	ALUXX-grade aluminum, 12x142mm thru-axle, flat mount disc, flip chip – dropout
GABEL	Advanced-grade composite, full-composite OverDrive steerer, 12mm thru-axle, flat mount disc
DÄMPFER	N/A
KOMPONENTEN	
LENKER	Giant Contact XR D-Fuse, 31.8mm, 5-degree back sweep, flare drop, XS: 400mm, S: 400mm, M: 420mm, L: 420mm
GRIFFE	Cork Tape w/ Gel VLT004-02
VORBAU	Giant Contact, 8-degree, XS: 50mm, S: 60mm, M: 70mm, L: 80mm
SATTELSTÜTZE	Giant D-Fuse, alloy
SATTEL	Liv Grit
ANTRIEB	
SCHALTHEBEL	Shimano GRX RX-610, 2x12
UMWERFER	Shimano GRX RX-820
SCHALTWERK	Shimano GRX RX-820
BREMSSEN	Shimano GRX BR-RX410 hydraulic, Giant MPH rotors, [F]160mm, [R]160mm
BREMSHEBEL	Shimano GRX RX-610 hydraulic
KASSETTE	Shimano 105, 12-speed, 11x34
KETTE	KMC X12L-1
KURBEL	Shimano FC-RX610, 30/46, XS: 165mm, S: 170mm, M: 172.5mm, L: 172.5mm
TRETLAGER	Shimano, press fit

LAUFRÄDER	
FELGEN	Giant S-X2 Disc, alloy
NABE	Giant alloy, 12mm thru-axle
SPEICHEN	stainless steel
REIFEN	CrossCut GRIP 1; 700x45c
EXTRAS	53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position, tubeless prepared, ISC clamp
LIMITS	
MAX TIRE CLEARANCE	53mm

GEOMETRIEDATEN

RAHMEN	XS	S	M	L
	SHORT LONG	SHORT LONG	SHORT LONG	SHORT LONG
Sitzrohrlänge (mm)	390	420	465	500
Sitzrohrwinkel	74.5° 74.4°	74.5° 74.4°	74.5° 74.4°	74.5° 74.4°
Oberrohrlänge (mm)	525 525	535 535	545 545	555 555
Steuerrohr-Länge (mm)	90	110	140	160
Steuerrohr-Winkel	70.0° 69.9°	70.5° 70.4°	71.0° 70.9°	71.0° 70.9°
Gabelneigung (mm)	50	50	50	50
Trail (mm)	78.4 82	75 78.5	71.6 75.1	71.6 75
Radstand (mm)	1017 1027	1024 1034	1031 1041	1043 1052
Kettenstreben-Länge (mm)	430 440	430 440	430 440	430 440
Tretlager-Höhe (mm)	80 81	80 81	80 81	80 81
Stack (mm)	523 524	544 545	574 575	593 594
Reach (mm)	380 379	384 383	386 385	391 389
Überstandshöhe (mm)	681 688	708 715	748 755	779 786
Lenkerbreite (mm)	400	400	420	420
Vorbaulänge (mm)	50	60	70	80
Kurbellänge (mm)	165	170	172.5	172.5

Spezifikations-, Preis- und Farbänderungen vorbehalten.