

DEVOTE 0



SPECIFICATIES

FRAME	
MATEN	XS, S, M, L
KLEUREN	Clear Sky
FRAME	ALUXX-grade aluminum, 12x142mm thru-axle, flat mount disc, flip chip – dropout
VOORVORK	Advanced-grade composite, full-composite OverDrive steerer, 12mm thru-axle, flat mount disc
DEMPER	N/A
ONDERDELEN	
STUUR	Giant Contact XR D-Fuse, 31.8mm, 5-degree back sweep, flare drop, XS: 400mm, S: 400mm, M: 420mm, L: 420mm
HANDVATTEN	Cork Tape w/ Gel VLT004-02
STUURPEN	Giant Contact, 8-degree, XS: 50mm, S: 60mm, M: 70mm, L: 80mm
ZADELPEEN	Giant D-Fuse, alloy
ZADEL	Liv Grit
AFMONTAGE	
SHIFTERS	Shimano GRX RX-610, 2x12
VOORDERAILLEUR	Shimano GRX RX-820
ACHTERDERAILLEUR	Shimano GRX RX-820
REMMEN	Shimano GRX BR-RX410 hydraulic, Giant MPH rotors, [F]160mm, [R]160mm
REMHENDELS	Shimano GRX RX-610 hydraulic
CASSETTE	Shimano 105, 12-speed, 11x34
AANDRIJVING	KMC X12L-1
CRANKSET	Shimano FC-RX610, 30/46, XS: 165mm, S: 170mm, M: 172.5mm, L: 172.5mm
BOTTOM BRACKET	Shimano, press fit

WIELSET	
VELGEN	Giant S-X2 Disc, alloy
NAVEN	Giant alloy, 12mm thru-axle
SPAKEN	stainless steel
BANDEN	CrossCut GRIP 1; 700x45c
EXTRA'S	53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position, tubeless prepared, ISC clamp
LIMITS	
MAXIMALE BANDENVRIJHEID	53mm

Adviesprijs: € 1.999,00

GEOMETRIE

FRAME	XS		S		M		L	
	SHORT LONG	SHORT LONG	SHORT LONG	SHORT LONG	SHORT LONG	SHORT LONG		
Zitbuis Lengte (mm)	390	420	465	500				
Zitbuis Hoek	74,5° 74,4°	74,5° 74,4°	74,5° 74,4°	74,5° 74,4°				
Frame Lengte (horizontaal) (mm)	525 525	535 535	545 545	555 555				
Balhoofdbuis Lengte (mm)	90	110	140	160				
Balhoofdbuis Hoek	70,0° 69,9°	70,5° 70,4°	71,0° 70,9°	71,0° 70,9°				
Vork Sprong (mm)	50	50	50	50				
Naloop (mm)	78,4 82	75 78,5	71,6 75,1	71,6 75				
Wielbasis (mm)	1017 1027	1024 1034	1031 1041	1043 1052				
Liggende achtervork lengte (mm)	430 440	430 440	430 440	430 440				
Bottom Bracket Drop (mm)	80 81	80 81	80 81	80 81				
Stack (mm)	523 524	544 545	574 575	593 594				
Reach (mm)	380 379	384 383	386 385	391 389				
Stand Over Height (mm)	681 688	708 715	748 755	779 786				
Stuur breedte (mm)	400	400	420	420				
Stuurpen Lengte (mm)	50	60	70	80				
Cranklengte (mm)	165	170	172,5	172,5				

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder voorafkondiging wijzigen.